

Material Safety Data Sheet

Equity

bp



1. Product and company identification

Product name DIESEL FUEL NO. 2
MSDS # 11155
Code 11155
Product use Fuel.
Synonyms Ultra Low Sulfur No. 2 Amoco Premier Diesel Fuel, Ultra Low Sulfur No. 2 Amoco Premier Diesel Fuel – Winterized, Ultra Low Sulfur No. 2 BP Supreme Diesel, Low Sulfur No. 2 BP Diesel Fuel, Ultra Low Sulfur No. 2 BP Diesel Fuel, Ultra Low Sulfur No. 2 BP Diesel Fuel – Winterized
Supplier BP Products North America Inc.
150 West Warrenville Road
Naperville, Illinois 60563-8460
USA
EMERGENCY HEALTH INFORMATION: 1 (800) 447-8735
Outside the US: +1 703-527-3887 (CHEMTREC)
EMERGENCY SPILL INFORMATION: 1 (800) 424-9300 CHEMTREC (USA)
OTHER PRODUCT INFORMATION 1 (866) 4 BP - MSDS
(866-427-6737 Toll Free - North America)
email: bpcares@bp.com

2. Hazards identification

Physical state Liquid.
Color Colorless. to Various Colors. (May be dyed Red., Light Green., Yellow.)
Emergency overview WARNING !
COMBUSTIBLE LIQUID AND VAPOR.
VAPOR MAY CAUSE FLASH FIRE.
HARMFUL IF SWALLOWED.
ASPIRATION HAZARD.
HARMFUL OR FATAL IF LIQUID IS ASPIRATED INTO LUNGS.
MAY CAUSE RESPIRATORY TRACT IRRITATION.
INHALATION CAUSES HEADACHES, DIZZINESS, DROWSINESS, AND NAUSEA, AND MAY LEAD TO UNCONSCIOUSNESS.
Combustible liquid. Harmful if swallowed. Aspiration hazard if swallowed. Can enter lungs and cause damage. Keep away from heat, sparks and flame. Avoid exposure - obtain special instructions before use. Do not breathe vapor or mist. Do not ingest. If ingested, do not induce vomiting. Avoid contact with eyes, skin and clothing. Contains material which may cause cancer, based on animal data. Risk of cancer depends on duration and level of exposure. Use only with adequate ventilation. Keep container tightly closed and sealed until ready for use. Wash thoroughly after handling.
Routes of entry Dermal contact. Eye contact. Inhalation. Ingestion.
Potential health effects
Eyes Slightly irritating to the eyes.
Skin Prolonged or repeated contact can defat the skin and lead to irritation and/or dermatitis.
Inhalation May cause respiratory tract irritation. Inhalation causes headaches, dizziness, drowsiness and nausea and may lead to unconsciousness. See toxicological information (section 11).

Product name DIESEL FUEL NO. 2

Product code 11155

Page: 1/8

Version 2 **Date of issue** 07/20/2010.

Format US-COMP

Language ENGLISH.

(US-COMP)

(ENGLISH)

Ingestion

Harmful if swallowed. Aspiration hazard if swallowed. Can enter lungs and cause damage. See toxicological information (section 11).

See toxicological information (section 11)

Composition/information on ingredients

ingredient name	CAS #	%
Petroleum distillates (Diesel Fuel No. 2)	68476-34-6	95 - 100
Contains one or more of the following biodiesels:	Varies	0 - 5
soybean oil, me ester	67784-80-9	.
Fatty acids, sunflower-oil, Me esters	68919-54-0	.
Fatty acids methyl esters	67762-38-3	.
Fatty acids, vegetable-oil, Methyl esters	68990-52-3	.
rape oil, me ester	73891-99-3	.
Fatty acids, canola-oil, Me esters	129828-16-6	.
fatty acids, tallow, me esters	61788-61-2	.
Contains:		
Naphthalene	91-20-3	1 - 3
May also contain small quantities of proprietary performance additives.		

4. First aid measures

Eye contact	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention.
Skin contact	Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention if irritation develops.
Inhalation	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.
Ingestion	Aspiration hazard if swallowed. Can enter lungs and cause damage. Do not induce vomiting. Never give anything by mouth to an unconscious person. Get medical attention immediately.

5. Fire-fighting measures

Flammability of the product	Combustible liquid.
Auto-ignition temperature	257°C (494°F)
Flash point	Closed cup: >38°C (>100.4°F) [Pensky-Martens.]
Explosion limits	Lower: 0.6% Upper: 7.5%
Fire/explosion hazards	Combustible liquid and vapor. Vapor may cause flash fire. Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. Runoff to sewer may create fire or explosion hazard.
Unusual fire/explosion hazards	Explosive in the presence of the following materials or conditions: open flames, sparks and static discharge and heat.
Extinguishing media	
Suitable	In case of fire, use water fog, foam, dry chemicals, or carbon dioxide.
Not suitable	Do not use water jet.
Fire-fighting procedures	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
Hazardous combustion products	Combustion products may include the following: carbon oxides (CO, CO ₂) (carbon monoxide, carbon dioxide)
Protective clothing (fire)	

Product name DIESEL FUEL NO. 2	Product code 11155	Page: 2/8
Version 2	Date of issue 07/20/2010.	Format US-COMP
	(US-COMP)	Language ENGLISH.
		(ENGLISH)

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Special remarks on fire hazards

Do not use water jet.

Accidental release measures

Environmental precautions

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Personal protection in case of a large spill

Chemical splash goggles. Chemical-resistant protective suit. Boots. Chemical-resistant gloves. Self-contained breathing apparatus (SCBA) should be used to avoid inhalation of the product. Suggested protective clothing might not be adequate. Consult a specialist before handling this product. CAUTION: The protection provided by air-purifying respirators is limited. Use a positive pressure air-supplied respirator if there is any potential for an uncontrolled release, if exposure levels are not known, or if concentrations exceed the protection limits of air-purifying respirator.

Methods for cleaning up

Large spill

Stop leak if without risk. Eliminate all ignition sources. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see section 1 for emergency contact information and section 13 for waste disposal.

Small spill

Stop leak if without risk. Eliminate all ignition sources. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor.

7. Handling and storage

Handling

Do not ingest. Never siphon by mouth. If ingested, do not induce vomiting. Put on appropriate personal protective equipment (see section 8). Workers should wash hands and face before eating, drinking and smoking. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use non-sparking tools. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material.

Storage

Store in accordance with local regulations. Store in a segregated and approved area. Store away from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10). Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

8. Exposure controls/personal protection

Occupational exposure limits

Ingredient name

Occupational exposure limits

Petroleum distillates

ACGIH TLV (United States). Absorbed through skin.

TWA: 100 mg/m³, (measured as total hydrocarbons) 8 hour(s). Issued/Revised: 1/2002 Form: Total hydrocarbons

Naphthalene

ACGIH TLV (United States).

STEL: 79 mg/m³ 15 minute(s). Issued/Revised: 5/1996

STEL: 15 ppm 15 minute(s). Issued/Revised: 5/1996

TWA: 52 mg/m³ 8 hour(s). Issued/Revised: 5/1996

TWA: 10 ppm 8 hour(s). Issued/Revised: 5/1996

OSHA PEL (United States).

TWA: 50 mg/m³ 8 hour(s). Issued/Revised: 6/1993

Product name DIESEL FUEL NO. 2

Product code 11155

Page: 3/8

Version 2 Date of issue 07/20/2010.

Format US-COMP

Language ENGLISH.

(US-COMP)

(ENGLISH)

While specific OELs for certain components may be shown in this section, other components may be present in any mist, vapor or dust produced. Therefore, the specific OELs may not be applicable to the product as a whole and are provided for guidance only.

Some states may enforce more stringent exposure limits.

Control Measures	Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.
Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing.
Personal protection	
Eyes	Avoid contact with eyes. Safety glasses with side shields.
Skin and body	Avoid contact with skin and clothing. Wear suitable protective clothing.
Respiratory	Use only with adequate ventilation. Do not breathe vapor or mist. If ventilation is inadequate, use a NIOSH-certified respirator with an organic vapor cartridge and P95 particulate filter. CAUTION: The protection provided by air-purifying respirators is limited. Use a positive pressure air-supplied respirator if there is any potential for an uncontrolled release, if exposure levels are not known, or if concentrations exceed the protection limits of air-purifying respirator.
Hands	Wear gloves that cannot be penetrated by chemicals or oil. The correct choice of protective gloves depends upon the chemicals being handled, the conditions of work and use, and the condition of the gloves (even the best chemically resistant glove will break down after repeated chemical exposures). Most gloves provide only a short time of protection before they must be discarded and replaced. Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. Gloves should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions. Consult your supervisor or Standard Operating Procedure (S.O.P) for special handling instructions.

Physical and chemical properties

Physical state	Liquid.
Color	Colorless. to Various Colors. (May be dyed Red., Light Green. , Yellow.)
Odor	Petroleum
Flash point	Closed cup: >38°C (>100.4°F) [Pensky-Martens.]
Explosion limits	Lower: 0.6% Upper: 7.5%
Auto-ignition temperature	257°C (494°F)
Specific gravity	<1 [Water = 1]
Density	820 to 875 kg/m ³ (0.82 to 0.875 g/cm ³)
Viscosity	Kinematic: 1.7 to 4.1 mm ² /s (1.7 to 4.1 cSt) at 40°C
Solubility	negligible <0.1%

10. Stability and reactivity

Stability and reactivity	Stable under recommended storage and handling conditions (see section 7).
Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	Keep away from heat, sparks and flame. Avoid all possible sources of ignition (spark or flame).
Incompatibility with various substances	Reactive or incompatible with the following materials: oxidizing materials, acids and alkalis. halogenated compounds.

Product name DIESEL FUEL NO. 2

Product code 11155

Page: 4/8

Version 2 Date of issue 07/20/2010.

Format US-COMP
(US-COMP)Language ENGLISH.
(ENGLISH)

Hazardous decomposition products carbon oxides (CO, CO₂) (carbon monoxide, carbon dioxide)

Hazardous polymerization Under normal conditions of storage and use, hazardous polymerization will not occur.

Toxicological information

Acute toxicity

Classification

Product/ingredient name	IARC	NTP	OSHA
Naphthalene	2B	Possible	-
fuel, diesel no. 2	3	-	-

IARC :
2B - Possible carcinogen to human.
3 - Not classifiable as a human carcinogen.

NTP :
Possible - Reasonably anticipated to be human carcinogens.

Other Toxicity Data Aspiration of this product into the lungs can cause chemical pneumonia and can be fatal. Aspiration into the lungs can occur while vomiting after ingestion of this product. Do not siphon by mouth.

Middle distillate: From skin-painting studies of petroleum distillates of similar composition and distillate range, it has been shown that these types of materials often possess weak carcinogenic activity in laboratory animals. In these tests, the material is painted on the shaved backs of mice twice a week for their lifetime. The material is not washed off between applications. Therefore, there may be a potential risk of skin cancer from prolonged or repeated skin contact with this product in the absence of good personal hygiene. This particular product has not been tested for carcinogenic activity, but we have chosen to be cautious in light of the findings with other distillate streams.

Occasional skin contact with this product is not expected to have serious effects, but good personal hygiene should be practiced and repeated skin contact avoided. This product can also be expected to produce skin irritation upon prolonged or repeated skin contact. Personal hygiene measures taken to prevent skin irritation are expected to be adequate to prevent risk of skin cancer.

Diesel exhaust particulates have been classified by the National Toxicological Program (NTP) to be a reasonably anticipated human carcinogen. Exposure should be minimized to reduce potential risk.

Naphthalene has been reported to cause developmental toxicity in mice after oral exposure to relatively high dose levels, but developmental toxicity was not observed in NTP (National Toxicology Program) sponsored studies in rats and rabbits. Ingestion or inhalation of naphthalene can result in hemolysis and other blood abnormalities, and individuals (and infants) deficient in glucose-6-phosphate dehydrogenase may be especially susceptible to these effects. Inhalation of naphthalene may cause headache and nausea. Airborne exposure can result in eye irritation. Naphthalene exposure has been associated with cataracts in animals and humans.

Other information

Potential chronic health effects

Carcinogenicity Contains material which may cause cancer, based on animal data. Risk of cancer depends on duration and level of exposure.

12. Ecological information

Ecotoxicity

No testing has been performed by the manufacturer.

Mobility Spillages may penetrate the soil causing ground water contamination.

Bioaccumulative potential This product is not expected to bioaccumulate through food chains in the environment.

Product name DIESEL FUEL NO. 2

Product code 11155

Page: 5/8

Version 2 Date of issue 07/20/2010.

Format US-COMP

Language ENGLISH.

(US-COMP)

(ENGLISH)

13. Disposal considerations

Waste information

The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

NOTE: The generator of waste has the responsibility for proper waste identification (based on characteristic(s) or listing), transportation and disposal

14. Transport information

International transport regulations

Regulatory information	UN number	Proper shipping name	Class	Packing group	Additional information
DOT Classification	NA 1993	Diesel fuel	3	III	-
TDG Classification	UN 1202	Gas oil	3	III	-
IMDG Classification	UN 1202	Gas oil	3	III	Remarks Marine pollutant
IATA/ICAO Classification	UN 1202	Gas oil	3	III	Remarks Environmentally hazardous substance mark.

15. Regulatory information

U.S. Federal Regulations

United States inventory (TSCA 8b)

All components are listed or exempted.

TSCA 12(b) one-time export: Naphthalene

SARA 302/304/311/312 extremely hazardous substances: No products were found.

SARA 302/304 emergency planning and notification: No products were found.

SARA 302/304/311/312 hazardous chemicals: Naphthalene

SARA 311/312 MSDS distribution - chemical inventory - hazard identification: DIESEL FUEL NO. 2: Fire hazard, Immediate (acute) health hazard, Delayed (chronic) health hazard

SARA 313

	Product name	CAS number	Concentration
Form R - Reporting requirements	Naphthalene	91-20-3	1.0035 - 3.0111
Supplier notification	Naphthalene	91-20-3	1.0035 - 3.0111
CERCLA Sections 102a/103 Hazardous Substances (40 CFR Part 302.4):	CERCLA: Hazardous substances.: o-Xylene: 1000 lbs. (454 kg); Naphthalene: 100 lbs. (45.4 kg); benzo[def]chrysene: 1 lb. (0.454 kg); Ethylbenzene: 1000 lbs. (454 kg); xylene: 100 lbs. (45.4 kg); Cumene: 5000 lbs. (2270 kg); Phenol: 1000 lbs. (454 kg); Benzene: 10 lbs. (4.54 kg); Alkylaryl sulfonic acid: 1000 lbs. (454 kg); Toluene: 1000 lbs. (454 kg); Methanol: 5000 lbs. (2270 kg); 2-Butoxyethanol;		

State regulations

Product name	DIESEL FUEL NO. 2	Product code	11155	Page:	6/8
Version	2	Date of issue	07/20/2010.	Format	US-COMP
				(US-COMP)	Language
					ENGLISH.
					(ENGLISH)

**Massachusetts
Substances**

The following components are listed: NAPHTHALENE

**New Jersey Hazardous
Substances**

The following components are listed: DIESEL FUEL; # 2 HEATING OIL; NAPHTHALENE; MOTH
FLAKES

**Pennsylvania RTK
Hazardous Substances**

The following components are listed: NAPHTHALENE

California Prop. 65

WARNING: This product contains a chemical known to the State of California to cause cancer.
Naphthalene; Ethylbenzene; benzo[def]chrysene

WARNING: This product contains a chemical known to the State of California to cause birth
defects or other reproductive harm.
Toluene

WARNING: This product contains a chemical known to the State of California to cause cancer and
birth defects or other reproductive harm.
Benzene

Prop 65 chemicals will result under certain conditions from the use of this material. For example,
burning fuels produces combustion products including diesel exhaust, a Prop 65 carcinogen, and
carbon monoxide, a Prop 65 reproductive toxin.

Inventories

Canada inventory	Not determined.
Europe inventory	At least one component is not listed.
Australia inventory (AICS)	At least one component is not listed.
China inventory (IECSC)	Not determined.
Japan inventory (ENCS)	At least one component is not listed.
Korea inventory (KECI)	At least one component is not listed.
Philippines inventory (PICCS)	At least one component is not listed.

Other information

Label requirements

WARNING !
 COMBUSTIBLE LIQUID AND VAPOR.
 VAPOR MAY CAUSE FLASH FIRE.
 HARMFUL IF SWALLOWED.
 ASPIRATION HAZARD.
 HARMFUL OR FATAL IF LIQUID IS ASPIRATED INTO LUNGS.
 MAY CAUSE RESPIRATORY TRACT IRRITATION.
 INHALATION CAUSES HEADACHES, DIZZINESS, DROWSINESS, AND NAUSEA, AND MAY
 LEAD TO UNCONSCIOUSNESS.

HMIS® Rating :

Health * 1
Flammability 2
Physical Hazard 0
Personal protection X

**National Fire
 Protection
 Association (U.S.A.)**



History

Date of issue 07/20/2010.
Date of previous issue 07/20/2010.
Prepared by Product Stewardship
Notice to reader

Product name DIESEL FUEL NO. 2

Product code 11155

Page: 7/8

Version 2 **Date of issue** 07/20/2010.

Format US-COMP
(US-COMP)

Language ENGLISH.
(ENGLISH)

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.

The data and advice given apply when the product is sold for the stated application or applications. You should not use the product for than for the stated application or applications without seeking advice from us.

is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The BP Group shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken.

Product name DIESEL FUEL NO. 2

Product code 11155

Page: 8/8

Version 2 Date of issue 07/20/2010.

Format US-COMP

Language ENGLISH.

(US-COMP)

(ENGLISH)

Material Safety Data Sheet



SECTION 1 PRODUCT AND COMPANY IDENTIFICATION

CHEVRON and TEXACO PREMIUM UNLEADED GASOLINES

Product Use: Fuel

Product Number(s): CPS201019 [See Section 16 for Additional Product Numbers]

Synonyms: Calco Premium Gasoline, Chevron Premium Unleaded Gasoline, Chevron Supreme Plus Unleaded Gasoline, Chevron Supreme Unleaded Gasoline, Gasolines, Automotive, Texaco Power Premium Unleaded Gasoline

Company Identification

Chevron Products Company
Marketing, MSDS Coordinator
6001 Bollinger Canyon Road
San Ramon, CA 94583
United States of America

Transportation Emergency Response

CHEMTREC: (800) 424-9300 or (703) 527-3887

Health Emergency

Chevron Emergency Information Center: Located in the USA. International collect calls accepted. (800) 231-0623 or (510) 231-0623

Product Information

MSDS Requests: <http://www.chevron.com/contact>
Technical Information: (510) 242-5357

SPECIAL NOTES: This MSDS applies to: all motor gasoline.

SECTION 2 COMPOSITION/ INFORMATION ON INGREDIENTS

COMPONENTS	CAS NUMBER	AMOUNT
Gasoline	86290-81-5	100 %vol/vol
Benzene	71-43-2	0.1 - 4.9 %vol/vol
Toluene (methylbenzene)	108-88-3	1 - 35 %vol/vol
Ethyl benzene	100-41-4	0.1 - 3 %vol/vol
Xylene (contains o-, m-, & p- xylene isomers in varying amounts)	1330-20-7	1 - 15 %vol/vol
Butane	106-97-8	1 - 12 %vol/vol
Heptane	142-82-5	1 - 4 %vol/vol
Hexane	110-54-3	1 - 5 %vol/vol
Cyclohexane	110-82-7	1 - 3 %vol/vol
Methylcyclohexane	108-87-2	1 - 2 %vol/vol
Pentane, 2,2,4-trimethyl- (Isooctane)	540-84-1	1 - 13 %vol/vol
Naphthalene	91-20-3	0.1 - 2 %vol/vol
Ethanol	64-17-5	0 - 10 %vol/vol
Methyl tert-butyl ether (MTBE)	1634-04-4	<= 0.1 %vol/vol

Motor gasoline is considered a mixture by EPA under the Toxic Substances Control Act (TSCA). The refinery streams used to blend motor gasoline are all on the TSCA Chemical Substances Inventory. The appropriate CAS number for refinery blended motor gasoline is 86290-81-5. The product specifications of motor gasoline sold in your area will depend on applicable Federal and State regulations.

SECTION 3 HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

- EXTREMELY FLAMMABLE LIQUID AND VAPOR. VAPOR MAY CAUSE FLASH FIRE
- HARMFUL OR FATAL IF SWALLOWED - MAY CAUSE LUNG DAMAGE IF SWALLOWED
- MAY CAUSE RESPIRATORY TRACT IRRITATION IF INHALED
- MAY CAUSE DIZZINESS, DROWSINESS AND REDUCED ALERTNESS
- CAUSES SKIN IRRITATION
- KEEP OUT OF REACH OF CHILDREN
- MAY CAUSE CANCER BASED ON ANIMAL DATA
- TOXIC TO AQUATIC ORGANISMS. MAY CAUSE LONG-TERM ADVERSE EFFECTS IN THE AQUATIC ENVIRONMENT

IMMEDIATE HEALTH EFFECTS

Eye: Not expected to cause prolonged or significant eye irritation.

Skin: Contact with the skin causes irritation. Skin contact may cause drying or defatting of the skin. Contact with the skin is not expected to cause an allergic skin response. Symptoms may include pain, itching, discoloration, swelling, and blistering. Not expected to be harmful to internal organs if absorbed through the skin.

Ingestion: Because of its low viscosity, this material can directly enter the lungs, if swallowed, or if subsequently vomited. Once in the lungs it is very difficult to remove and can cause severe injury or death.

Inhalation: The vapor or fumes from this material may cause respiratory irritation. Symptoms of respiratory irritation may include coughing and difficulty breathing. Excessive or prolonged breathing of this material may cause central nervous system effects. Central nervous system effects may include headache, dizziness, nausea, vomiting, weakness, loss of coordination, blurred vision, drowsiness, confusion, or disorientation. At extreme exposures, central nervous system effects may include respiratory depression, tremors or convulsions, loss of consciousness, coma or death.

DELAYED OR OTHER HEALTH EFFECTS:

Reproduction and Birth Defects: This material is not expected to cause birth defects or other harm to the developing fetus based on animal data.

Cancer: Prolonged or repeated exposure to this material may cause cancer. Contains naphthalene, which has been classified as a Group 2B carcinogen (possibly carcinogenic to humans) by the International Agency for Research on Cancer (IARC). Gasoline has been classified as a Group 2B carcinogen (possibly carcinogenic to humans) by the International Agency for Research on Cancer (IARC).

Contains benzene, which has been classified as a carcinogen by the National Toxicology Program (NTP) and a Group 1 carcinogen (carcinogenic to humans) by the International Agency for Research on Cancer (IARC).

Contains ethylbenzene which has been classified as a Group 2B carcinogen (possibly carcinogenic to humans) by the International Agency for Research on Cancer (IARC).

Whole gasoline exhaust has been classified as a Group 2B carcinogen (possibly carcinogenic to humans)

by the International Agency for Research on Cancer (IARC).

Risk depends on duration and level of exposure. See Section 11 for additional information.

SECTION 4 FIRST AID MEASURES

Eye: No specific first aid measures are required. As a precaution, remove contact lenses, if worn, and flush eyes with water.

Skin: Wash skin with water immediately and remove contaminated clothing and shoes. Get medical attention if any symptoms develop. To remove the material from skin, use soap and water. Discard contaminated clothing and shoes or thoroughly clean before reuse.

Ingestion: If swallowed, get immediate medical attention. Do not induce vomiting. Never give anything by mouth to an unconscious person.

Inhalation: Move the exposed person to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention if breathing difficulties continue or if any other symptoms develop.

Note to Physicians: Ingestion of this product or subsequent vomiting may result in aspiration of light hydrocarbon liquid, which may cause pneumonitis.

SECTION 5 FIRE FIGHTING MEASURES

See Section 7 for proper handling and storage.

FIRE CLASSIFICATION:

OSHA Classification (29 CFR 1910.1200): Flammable liquid.

NFPA RATINGS: Health: 1 Flammability: 3 Reactivity: 0

FLAMMABLE PROPERTIES:

Flashpoint: (Tagliabue Closed Cup ASTM D56) < -45 °C (< -49 °F)

Autoignition: > 280 °C (> 536 °F)

Flammability (Explosive) Limits (% by volume in air): Lower: 1.4 Upper: 7.6 (Typical)

EXTINGUISHING MEDIA: Dry Chemical, CO₂, AFFF Foam or alcohol resistant foam if >15% volume polar solvents (oxygenates).

PROTECTION OF FIRE FIGHTERS:

Fire Fighting Instructions: Use water spray to cool fire-exposed containers and to protect personnel. For fires involving this material, do not enter any enclosed or confined fire space without proper protective equipment, including self-contained breathing apparatus.

Combustion Products: Highly dependent on combustion conditions. A complex mixture of airborne solids, liquids, and gases including carbon monoxide, carbon dioxide, and unidentified organic compounds will be evolved when this material undergoes combustion.

SECTION 6 ACCIDENTAL RELEASE MEASURES

Protective Measures: Eliminate all sources of ignition in the vicinity of the spill or released vapor. If this material is released into the work area, evacuate the area immediately. Monitor area with combustible gas indicator.

Spill Management: Stop the source of the release if you can do it without risk. Contain release to prevent further contamination of soil, surface water or groundwater. Clean up spill as soon as possible, observing precautions in Exposure Controls/Personal Protection. Use appropriate techniques such as applying

non-combustible absorbent materials or pumping. All equipment used when handling the product must be grounded. A vapor suppressing foam may be used to reduce vapors. Use clean non-sparking tools to collect absorbed material. Where feasible and appropriate, remove contaminated soil. Place contaminated materials in disposable containers and dispose of in a manner consistent with applicable regulations.

Reporting: Report spills to local authorities and/or the U.S. Coast Guard's National Response Center at (800) 424-8802 as appropriate or required. This material is covered by EPA's Comprehensive Environmental Response, Compensation and Liability Act (CERCLA) Petroleum Exclusion. Therefore, releases to the environment may not be reportable under CERCLA.

SECTION 7 HANDLING AND STORAGE

Precautionary Measures: This product presents an extreme fire hazard. Liquid very quickly evaporates, even at low temperatures, and forms vapor (fumes) which can catch fire and burn with explosive violence. Invisible vapor spreads easily and can be set on fire by many sources such as pilot lights, welding equipment, and electrical motors and switches. Never siphon gasoline by mouth.

Do not store in open or unlabeled containers. READ AND OBSERVE ALL PRECAUTIONS ON PRODUCT LABEL. Do not get in eyes, on skin, or on clothing. Use only as a motor fuel. Do not use for cleaning, pressure appliance fuel, or any other such use. Do not taste or swallow. Do not breathe vapor or fumes. Wash thoroughly after handling. Keep out of the reach of children.

Unusual Handling Hazards: WARNING! Do not use as portable heater or appliance fuel. Toxic fumes may accumulate and cause death.

General Handling Information: Avoid contaminating soil or releasing this material into sewage and drainage systems and bodies of water.

Static Hazard: Electrostatic charge may accumulate and create a hazardous condition when handling this material. To minimize this hazard, bonding and grounding may be necessary but may not, by themselves, be sufficient. Review all operations which have the potential of generating and accumulating an electrostatic charge and/or a flammable atmosphere (including tank and container filling, splash filling, tank cleaning, sampling, gauging, switch loading, filtering, mixing, agitation, and vacuum truck operations) and use appropriate mitigating procedures. For more information, refer to OSHA Standard 29 CFR 1910.106, 'Flammable and Combustible Liquids', National Fire Protection Association (NFPA 77, 'Recommended Practice on Static Electricity', and/or the American Petroleum Institute (API) Recommended Practice 2003, 'Protection Against Ignitions Arising Out of Static, Lightning, and Stray Currents'. Improper filling of portable gasoline containers creates danger of fire. Only dispense gasoline into approved and properly labeled gasoline containers. Always place portable containers on the ground. Be sure pump nozzle is in contact with the container while filling. Do not use a nozzle's lock-open device. Do not fill portable containers that are inside a vehicle or truck/trailer bed.

General Storage Information: DO NOT USE OR STORE near heat, sparks, flames, or hot surfaces . USE AND STORE ONLY IN WELL VENTILATED AREA. Keep container closed when not in use.

Container Warnings: Container is not designed to contain pressure. Do not use pressure to empty container or it may rupture with explosive force. Empty containers retain product residue (solid, liquid, and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. They may explode and cause injury or death. Empty containers should be completely drained, properly closed, and promptly returned to a drum reconditioner or disposed of properly.

SECTION 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

GENERAL CONSIDERATIONS:

Consider the potential hazards of this material (see Section 3), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting personal protective equipment. If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should

read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstances.

ENGINEERING CONTROLS:

Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below the recommended exposure limits.

PERSONAL PROTECTIVE EQUIPMENT

Eye/Face Protection: No special eye protection is normally required. Where splashing is possible, wear safety glasses with side shields as a good safety practice.

Skin Protection: Wear protective clothing to prevent skin contact. Selection of protective clothing may include gloves, apron, boots, and complete facial protection depending on operations conducted.

Suggested materials for protective gloves include: Chlorinated Polyethylene (or Chlorosulfonated Polyethylene), Nitrile Rubber, Polyurethane, Viton.

Respiratory Protection: Determine if airborne concentrations are below the recommended occupational exposure limits for jurisdiction of use. If airborne concentrations are above the acceptable limits, wear an approved respirator that provides adequate protection from this material, such as: Air-Purifying Respirator for Organic Vapors.

When used as a fuel, this material can produce carbon monoxide in the exhaust. Determine if airborne concentrations are below the occupational exposure limit for carbon monoxide. If not, wear an approved positive-pressure air-supplying respirator.

Use a positive pressure air-supplying respirator in circumstances where air-purifying respirators may not provide adequate protection.

Occupational Exposure Limits:

Component	Agency	TWA	STEL	Ceiling	Notation
Benzene	ACGIH	.5 ppm (weight)	2.5 ppm (weight)	--	Skin A1 Skin
Benzene	CVX	1 ppm (weight)	5 ppm (weight)	--	--
Benzene	OSHA SRS	1 ppm (weight)	5 ppm (weight)	--	--
Benzene	OSHA Z-2	10 ppm (weight)	--	25 ppm (weight)	--
Butane	ACGIH	1000 ppm (weight)	--	--	--
Cyclohexane	ACGIH	100 ppm (weight)	--	--	--
Cyclohexane	OSHA Z-1	1050 mg/m3	--	--	--
Ethanol	ACGIH	1000 ppm (weight)	--	--	A4 A3
Ethanol	OSHA Z-1	1900 mg/m3	--	--	--
Ethyl benzene	ACGIH	20 ppm (weight)	125 ppm (weight)	--	A3
Ethyl benzene	OSHA Z-1	435 mg/m3	--	--	--
Gasoline	ACGIH	300 ppm (weight)	500 ppm (weight)	--	A3
Heptane	ACGIH	400 ppm (weight)	500 ppm (weight)	--	--
Heptane	OSHA Z-1	2000 mg/m3	--	--	--
Hexane	ACGIH	50 ppm (weight)	--	--	Skin
Hexane	OSHA Z-1	1800 mg/m3	--	--	--
Methyl tert-butyl ether (MTBE)	ACGIH	50 ppm	--	--	A3

		(weight)			
Methyl tert-butyl ether (MTBE)	CVX	--	50 ppm	--	--
Methylcyclohexane	ACGIH	400 ppm (weight)	--	--	--
Methylcyclohexane	OSHA Z-1	2000 mg/m3	--	--	--
Naphthalene	ACGIH	10 ppm (weight)	15 ppm (weight)	--	Skin
Naphthalene	OSHA Z-1	50 mg/m3	--	--	--
Pentane, 2,2,4-trimethyl- (Isooctane)	ACGIH	300 ppm (weight)	--	--	--
Pentane, 2,2,4-trimethyl- (Isooctane)	OSHA Z-1	2350 mg/m3	--	--	--
Toluene (methylbenzene)	ACGIH	50 ppm (weight)	--	--	Skin A4
Toluene (methylbenzene)	OSHA Z-2	200 ppm (weight)	--	300 ppm (weight)	--
Xylene (contains o-, m-, & p- xylene isomers in varying amounts)	ACGIH	100 ppm (weight)	150 ppm (weight)	--	A4
Xylene (contains o-, m-, & p- xylene isomers in varying amounts)	OSHA Z-1	435 mg/m3	--	--	--

Refer to the OSHA Benzene Standard (29 CFR 1910.1028) and Table Z-2 for detailed training, exposure monitoring, respiratory protection and medical surveillance requirements before using this product. Consult local authorities for appropriate values.

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Attention: the data below are typical values and do not constitute a specification.

Color: Colorless to yellow

Physical State: Liquid

Odor: Petroleum odor

pH: Not Applicable

Vapor Pressure: 5 psi - 15 psi (Typical) @ 37.8 °C (100 °F)

Vapor Density (Air = 1): 3 - 4 (Typical)

Boiling Point: 37.8°C (100°F) - 204.4°C (400°F) (Typical)

Solubility: Insoluble in water; miscible with most organic solvents.

Freezing Point: Not Applicable

Melting Point: Not Applicable

Specific Gravity: 0.7 g/ml - 0.8 g/ml @ 15.6°C (60.1°F) (Typical)

Viscosity: <1 SUS @ 37.8°C (100°F)

Evaporation Rate: No data available

SECTION 10 STABILITY AND REACTIVITY

Chemical Stability: This material is considered stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

Incompatibility With Other Materials: May react with strong acids or strong oxidizing agents, such as chlorates, nitrates, peroxides, etc.

Hazardous Decomposition Products: None known (None expected)

Hazardous Polymerization: Hazardous polymerization will not occur.

SECTION 11 TOXICOLOGICAL INFORMATION

IMMEDIATE HEALTH EFFECTS

Eye Irritation: The eye irritation hazard is based on evaluation of data for similar materials or product components.

Skin Irritation: For a 4-hour exposure, the Primary Irritation Index (PII) in rabbits is: 4.8/8.0.

Skin Sensitization: This material did not cause skin sensitization reactions in a Buehler guinea pig test.

Acute Dermal Toxicity: LD50: >3.75g/kg (rabbit).

Acute Oral Toxicity: LD50: >5 ml/kg (rat)

Acute Inhalation Toxicity: 4 hour(s) LD50: >20000mg/m³ (rat).

Subchronic Effects: Exposure of rats for 13 weeks (6 hr/day for 5 days/week) to the light ends of gasoline (up to 20,000 mg/m³) resulted in minimal responses of toxicity. There were no indications of neurotoxicity based morphological, functional and biochemical indices. There was also no evidence of immunotoxicity in the rats. However, when rats were exposed to gasoline vapor containing ethanol up to 20,000 mg/m³ there was evidence of both humoral immune suppression and mild astrogliosis.

Reproduction and Birth Defects: Exposure of rats to the light ends of gasoline at up to 20,000 mg/m³ had generally no impact upon reproductive abilities and did not cause birth defects. **Genetic Toxicity:** Gasoline was not mutagenic, with or without activation, in the Ames assay (Salmonella typhimurium), Saccharomyces cerevisiae, or mouse lymphoma assays. In addition, point mutations were not induced in human lymphocytes. Gasoline was not mutagenic when tested in the mouse dominant lethal assay. Administration of gasoline to rats did not cause chromosomal aberrations in their bone marrow cells. Inhalation exposure of rats to the light ends of gasoline caused increased sister chromatid exchange in their peripheral white blood cells but did not cause an increase in micronucleated red blood cells in their bone marrow.

ADDITIONAL TOXICOLOGY INFORMATION:

Gasolines are highly volatile and can produce significant concentrations of vapor at ambient temperatures. Gasoline vapor is heavier than air and at high concentrations may accumulate in confined spaces to present both safety and health hazards. When vapor exposures are low, or short duration and infrequent, such as during refueling and tanker loading/unloading, neither total hydrocarbon nor components such as benzene are likely to result in any adverse health effects. In situations such as accidents or spills where exposure to gasoline vapor is potentially high, attention should be paid to potential toxic effects of specific components. Information about specific components in gasoline can be found in Sections 2/3, 8 and 15 of this MSDS. More detailed information on the health hazard of specific gasoline components can be obtained calling the Chevron Emergency Information Center (see Section 1 for phone numbers). Pathological misuse of solvents and gasoline, involving repeated and prolonged exposure to high concentrations of vapor is a significant exposure on which there are many reports in the medical literature. As with other solvents, persistent abuse involving repeated and prolonged exposures to high concentrations of vapor has been reported to result in central nervous system damage and eventually, death. In a study in which ten human volunteers were exposed for 30 minutes to approximately 200, 500 or 1000 ppm concentrations of gasoline vapor, irritation of the eyes was the only significant effect observed, based on both subjective and objective assessments.

Lifetime inhalation of wholly vaporized unleaded gasoline at 2056 ppm has caused increased liver tumors in female mice and kidney cancer in male rats. In their 1988 review of carcinogenic risk from gasoline, The International Agency for Research on Cancer (IARC) noted that, because published epidemiology studies did not include any exposure data, only occupations where gasoline exposure may have occurred were reviewed. These included gasoline service station attendants and automobile mechanics. IARC also noted that there was no opportunity to separate effects of combustion products from those of gasoline itself. Although IARC allocated gasoline a final overall classification of Group 2B, i.e. possibly carcinogenic to humans, this was based on limited evidence in experimental animals plus supporting evidence including the presence in gasoline of benzene. The actual evidence for carcinogenicity in humans was considered inadequate.

To explore the health effects of workers potentially exposed to gasoline vapors in the marketing and distribution sectors of the petroleum industry, the American Petroleum Institute sponsored a cohort mortality study (Publication 4555), a nested case-control study (Publication 4551), and an exposure assessment study (Publication 4552). Histories of exposure to gasoline were reconstructed for cohort of more than

18,000 employees from four companies for the time period between 1946 and 1985. The results of the cohort mortality study indicated that there was no increased mortality from either kidney cancer or leukemia among marketing and marine distribution employees who were exposed to gasoline in the petroleum industry, when compared to the general population. More importantly, based on internal comparisons, there was no association between mortality from kidney cancer or leukemia and various indices of gasoline exposure. In particular, neither duration of employment, duration of exposure, age at first exposure, year of first exposure, job category, cumulative exposure, frequency of peak exposure, nor average intensity of exposure had any effect on kidney cancer or leukemia mortality. The results of the nested case-control study confirmed the findings of the original cohort study. That is, exposure to gasoline at the levels experienced by this cohort of distribution workers is not a significant risk factor for leukemia (all cell types), acute myeloid leukemia, kidney cancer or multiple myeloma.

SECTION 12 ECOLOGICAL INFORMATION

ECOTOXICITY

96 hour(s) LC50: 2.7 mg/l (Oncorhynchus mykiss)

48 hour(s) LC50: 3.0 mg/l (Daphnia magna)

96 hour(s) LC50: 8.3 mg/l (Cyprinodon variegatus)

96 hour(s) LC50: 1.8 mg/l (Mysidopsis bahia)

This material is expected to be toxic to aquatic organisms and may cause long-term adverse effects in the aquatic environment. Gasoline studies have been conducted in the laboratory under a variety of test conditions with a range of fish and invertebrate species. An even more extensive database is available on the aquatic toxicity of individual aromatic constituents. The majority of published studies do not identify the type of gasoline evaluated, or even provide distinguishing characteristics such as aromatic content or presence of lead alkyls. As a result, comparison of results among studies using open and closed vessels, different ages and species of test animals and different gasoline types, is difficult.

The bulk of the available literature on gasoline relates to the environmental impact of monoaromatic (BTEX) and diaromatic (naphthalene, methylnaphthalenes) constituents. In general, non-oxygenated gasoline exhibits some short-term toxicity to freshwater and marine organisms, especially under closed vessel or flow-through exposure conditions in the laboratory. The components which are the most prominent in the water soluble fraction and cause aquatic toxicity, are also highly volatile and can be readily biodegraded by microorganisms.

The ecotoxicity hazard is based on an evaluation of data for the components or a similar material.

ENVIRONMENTAL FATE

Ready Biodegradability: This material is expected to be readily biodegradable. Following spillage, the more volatile components of gasoline will be rapidly lost, with concurrent dissolution of these and other constituents into the water. Factors such as local environmental conditions (temperature, wind, mixing or wave action, soil type, etc), photo-oxidation, biodegradation and adsorption onto suspended sediments, can contribute to the weathering of spilled gasoline.

The aqueous solubility of non-oxygenated unleaded gasoline, based on analysis of benzene, toluene, ethylbenzene+xylenes and naphthalene, is reported to be 112 mg/l. Solubility data on individual gasoline constituents also available.

The biodegradability of this material is based on an evaluation of data for the components or a similar material.

SECTION 13 DISPOSAL CONSIDERATIONS

Use material for its intended purpose or recycle if possible. This material, if it must be discarded, may meet the criteria of a hazardous waste as defined by US EPA under RCRA (40 CFR 261) or other State and local regulations. Measurement of certain physical properties and analysis for regulated components may be necessary to make a correct determination. If this material is classified as a hazardous waste, federal law requires disposal at a licensed hazardous waste disposal facility.

SECTION 14 TRANSPORT INFORMATION

The description shown may not apply to all shipping situations. Consult 49CFR, or appropriate Dangerous Goods Regulations, for additional description requirements (e.g., technical name) and mode-specific or quantity-specific shipping requirements.

DOT Shipping Description: UN1203, GASOLINE, 3, II; OPTIONAL DISCLOSURE: UN1203, GASOLINE, 3, II, MARINE POLLUTANT (GASOLINE)

IMO/IMDG Shipping Description: UN1203, GASOLINE, 3, II, FLASH POINT SEE SECTION 5 OR 9, MARINE POLLUTANT (GASOLINE)

ICAO/IATA Shipping Description: UN1203, GASOLINE, 3, II

SECTION 15 REGULATORY INFORMATION

EPCRA 311/312 CATEGORIES:	1. Immediate (Acute) Health Effects:	YES
	2. Delayed (Chronic) Health Effects:	YES
	3. Fire Hazard:	YES
	4. Sudden Release of Pressure Hazard:	NO
	5. Reactivity Hazard:	NO

REGULATORY LISTS SEARCHED:

01-1=IARC Group 1	03=EPCRA 313
01-2A=IARC Group 2A	04=CA Proposition 65
01-2B=IARC Group 2B	05=MA RTK
02=NTP Carcinogen	06=NJ RTK
	07=PA RTK

The following components of this material are found on the regulatory lists indicated.

Benzene	01-1, 02, 03, 04, 05, 06, 07
Butane	05, 06, 07
Cyclohexane	03, 05, 06, 07
Ethanol	01-1, 02, 04, 05, 06, 07
Ethyl benzene	01-2B, 03, 04, 05, 06, 07
Gasoline	01-2B, 06, 07
Heptane	05, 06, 07
Hexane	03, 05, 06, 07
Methyl tert-butyl ether (MTBE)	03, 05, 06, 07
Methylcyclohexane	05, 06, 07
Naphthalene	01-2B, 02, 03, 04, 05, 06, 07
Pentane, 2,2,4-trimethyl- (Isooctane)	05, 06, 07
Toluene (methylbenzene)	03, 04, 05, 06, 07
Xylene (contains o-, m-, & p- xylene isomers in varying amounts)	03, 05, 06, 07

CERCLA REPORTABLE QUANTITIES(RQ)/EPCRA 302 THRESHOLD PLANNING QUANTITIES(TPQ):

Component	Component RQ	Component TPQ	Product RQ
Benzene	10 lbs	None	186 lbs
Cyclohexane	1000 lbs	None	34188 lbs
Ethyl benzene	1000 lbs	None	34964 lbs
Hexane	5000 lbs	None	129149 lbs
Methyl tert-butyl ether (MTBE)	1000 lbs	None	1080351 lbs
Naphthalene	100 lbs	None	4000 lbs
Pentane, 2,2,4-trimethyl- (Isooctane)	1000 lbs	None	6270 lbs
Toluene (methylbenzene)	1000 lbs	None	2627 lbs
Xylene (contains o-, m-, & p- xylene isomers in varying amounts)	100 lbs	None	649 lbs

CHEMICAL INVENTORIES:

All components comply with the following chemical inventory requirements: AICS (Australia), DSL (Canada), EINECS (European Union), ENCS (Japan), IECSC (China), KECI (Korea), PICCS (Philippines), TSCA (United States).

SECTION 16 OTHER INFORMATION

NFPA RATINGS: Health: 1 Flammability: 3 Reactivity: 0

HMIS RATINGS: Health: 2* Flammability: 3 Reactivity: 0

(0-Least, 1-Slight, 2-Moderate, 3-High, 4-Extreme, PPE:- Personal Protection Equipment Index recommendation, *- Chronic Effect Indicator). These values are obtained using the guidelines or published evaluations prepared by the National Fire Protection Association (NFPA) or the National Paint and Coating Association (for HMIS ratings).

Additional Product Number(s): CPS201024, CPS201050, CPS201051, CPS201058, CPS201060, CPS201061, CPS201066, CPS201068, CPS201069, CPS201071, CPS201072, CPS201078, CPS201081, CPS201084, CPS201085, CPS201088, CPS201091, CPS201092, CPS201094, CPS201096, CPS201097, CPS201098, CPS201101, CPS201103, CPS201114, CPS201117, CPS201193, CPS201213, CPS201214, CPS201215, CPS201233, CPS201234, CPS201235, CPS201263, CPS201264, CPS201265, CPS201274, CPS201275, CPS201276, CPS201283, CPS201284, CPS201285, CPS201293, CPS201294, CPS201295, CPS201853, CPS201854, CPS201861, CPS201862, CPS201863, CPS204006, CPS204007, CPS204008, CPS204009, CPS204014, CPS204015, CPS204026, CPS204027, CPS204050, CPS204051, CPS204074, CPS204075, CPS204092, CPS204093, CPS204108, CPS204109, CPS204120, CPS204121, CPS204144, CPS204145, CPS204168, CPS204169, CPS204192, CPS204193, CPS204204, CPS204205, CPS204211, CPS204216, CPS204217, CPS204228, CPS204229, CPS204252, CPS204253, CPS204276, CPS204277, CPS204294, CPS204295, CPS204327, CPS204328, CPS204329, CPS204351, CPS204353, CPS204355, CPS204357, CPS204362, CPS204363, CPS204368, CPS204369, CPS204374, CPS204375, CPS204380, CPS204381, CPS204386, CPS204387, CPS204392, CPS204393, CPS204398, CPS204399, CPS204404, CPS204405, CPS204410, CPS204411, CPS204416, CPS204417, CPS204422, CPS204423, CPS204428, CPS204429, CPS204434, CPS204435, CPS204440, CPS204441, CPS204443, CPS204447, CPS204451, CPS204455, CPS204459, CPS204463, CPS204470, CPS204471, CPS204488, CPS204489, CPS204506, CPS204507, CPS204524, CPS204525, CPS204542, CPS204543, CPS204560, CPS204561, CPS204578, CPS204579, CPS204596, CPS204597, CPS204614, CPS204615, CPS204632, CPS204633, CPS204650, CPS204651, CPS204668, CPS204669, CPS204683, CPS204694, CPS204695, CPS204700, CPS204701, CPS204706, CPS204707, CPS204712, CPS204713, CPS204725, CPS204726, CPS204731, CPS204732, CPS204741, CPS241766

REVISION STATEMENT: This revision updates the following sections of this Safety Data Sheet: 14
Revision Date: March 03, 2014

ABBREVIATIONS THAT MAY HAVE BEEN USED IN THIS DOCUMENT:

TLV - Threshold Limit Value	TWA - Time Weighted Average
STEL - Short-term Exposure Limit	PEL - Permissible Exposure Limit
	CAS - Chemical Abstract Service Number
ACGIH - American Conference of Governmental Industrial Hygienists	IMO/IMDG - International Maritime Dangerous Goods Code
API - American Petroleum Institute	MSDS - Material Safety Data Sheet
CVX - Chevron	NFPA - National Fire Protection Association (USA)
DOT - Department of Transportation (USA)	NTP - National Toxicology Program (USA)
IARC - International Agency for Research on Cancer	OSHA - Occupational Safety and Health Administration
NCEL - New Chemical Exposure Limit	EPA - Environmental Protection Agency
SCBA - Self-Contained Breathing Apparatus	

Prepared according to the 29 CFR 1910.1200 (2012) by Chevron Energy Technology Company, 6001 Bollinger Canyon Road San Ramon, CA 94583.

The above information is based on the data of which we are aware and is believed to be correct as of the date hereof. Since this information may be applied under conditions beyond our control and with which we may be unfamiliar and since data made available subsequent to the date hereof may suggest modifications of the information, we do not assume any responsibility for the results of its use. This information is furnished upon condition that the person receiving it shall make his own determination of the suitability of the material for his particular purpose.

MATERIAL SAFETY DATA SHEET

SECTION 1 PRODUCT AND COMPANY IDENTIFICATION

PRODUCT

Product Name: (see Section 16 for Synonyms) **GASOLINE UNLEADED WITH ETHANOL (GASOHOL)**
Product Description: Hydrocarbons and Additives
MSDS Number: 12443

Intended Use: Fuel

COMPANY IDENTIFICATION

Supplier: Imperial Oil Products Division
 240 4th Avenue
 Calgary, ALBERTA. T2P 3M9 Canada
24 Hour Environmental / Health Emergency Telephone 1-866-232-9563
Transportation Emergency Phone Number 1-866-232-9563
Product Technical Information 1-800-268-3183
Supplier General Contact 1-800-567-3776

SECTION 2 COMPOSITION / INFORMATION ON INGREDIENTS

Reportable Hazardous Substance(s) or Complex Substance(s)

Name	CAS#	Concentration*	Acute Toxicity
ETHYL ALCOHOL	64-17-5	5 - 10%	Inhalation Lethality: LC50 20000 ppm (Rat); Oral Lethality: LD50 7.06 g/kg (Rat)
GASOLINE	86290-81-5	85 - 95%	None
METHYL-TERT-BUTYL ETHER	1634-04-4	0 - 7%	Dermal Lethality: LD50 > 10.0 g/kg (Rabbit); Inhalation Lethality: LC50 85 mg/l (Rat); Oral Lethality: LD50 4.0 g/kg (Rat)

Hazardous Constituent(s) Contained in Complex Substance(s)

Name	CAS#	Concentration*	Acute Toxicity
BENZENE	71-43-2	0 - 1.5%	Dermal Lethality: LD50 > 9.4 g/kg (Rabbit); Inhalation Lethality: LC50 43.7 mg/l (Rat); Oral Lethality: LD50 > 2000 mg/kg (Rat)
CUMENE	98-82-8	0 - 1%	Dermal Lethality: LD50 10.6 g/kg (Rabbit); Inhalation Lethality: LC50 8000 ppm (Rat); Oral Lethality: LD50 1.4 g/kg (Rat)
CYCLOHEXANE	110-82-7	0 - 1%	Dermal Lethality: LD50 > 2000 mg/kg (Rabbit); Inhalation Lethality: LC50 > 19.1 mg/l (Rat)

ETHYL BENZENE	100-41-4	0 - 3%	Inhalation Lethality: LC50 17.8 mg/l (Rat); Oral Lethality: LD50 3.5 g/kg (Rat)
n-Hexane	110-54-3	0 - 3%	Dermal Lethality: LD50 > 2000 mg/kg (Rabbit); Inhalation Lethality: LC50 > 17.6 mg/l (Rat)
NAPHTHALENE	91-20-3	0 - 1%	Dermal Lethality: LD50 > 2500 mg/kg (Rat); Inhalation Lethality: LC50 > 0.4 mg/l (Rat); Oral Lethality: LD50 622 mg/kg (Mouse)
TOLUENE	108-88-3	0 - 20%	Dermal Lethality: LD50 12.10 g/kg (Rabbit); Inhalation Lethality: LC50 8000 ppm (Rat); Oral Lethality: LD50 5.0 g/kg (Rat)
XYLENES	1330-20-7	0 - 10%	Oral Lethality: LD50 > 5000 mg/kg (Rat)

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

NOTE: The concentration of the components shown above may vary substantially. In certain countries, benzene content may be limited to lower levels. Oxygenates such as tertiary-amyl-methyl ether, ethanol, di-isopropyl ether, and ethyl-tertiary-butyl ether may be present. Because of volatility considerations, gasoline vapor may have concentrations of components very different from those of liquid gasoline. The major components of gasoline vapor are: butane, isobutane, pentane, and isopentane. The reportable component percentages, shown in the composition/information on ingredients section, are based on API's evaluation of a typical gasoline mixture.

SECTION 3 HAZARDS IDENTIFICATION

This material is considered to be hazardous according to regulatory guidelines (see (M)SDS Section 15).

PHYSICAL/CHEMICAL EFFECTS

FLAMMABLE. Material can release vapours that readily form flammable mixtures. Vapour accumulation could flash and/or explode if ignited. Material can accumulate static charges which may cause an ignition.

HEALTH EFFECTS

May cause cancer. Repeated exposure may cause skin dryness or cracking. If swallowed, may be aspirated and cause lung damage. May be irritating to the eyes, nose, throat, and lungs. May cause central nervous system depression. High-pressure injection under skin may cause serious damage. Prolonged and repeated exposure to benzene may cause serious injury to blood forming organs and is associated with anaemia and to the later development of acute myelogenous leukaemia (AML).

Target Organs: Blood and/or blood-forming organs |

NFPA Hazard ID: Health: 1 Flammability: 3 Reactivity: 0
 HMIS Hazard ID: Health: 1* Flammability: 3 Reactivity: 0

NOTE: This material should not be used for any other purpose than the intended use in Section 1 without expert advice. Health studies have shown that chemical exposure may cause potential human health risks which may vary from person to person.

SECTION 4 FIRST AID MEASURES

INHALATION

Remove from further exposure. For those providing assistance, avoid exposure to yourself or others. Use adequate respiratory protection. If respiratory irritation, dizziness, nausea, or unconsciousness occurs, seek immediate medical assistance. If breathing has stopped, assist ventilation with a mechanical device or use mouth-to-mouth resuscitation.

SKIN CONTACT

Wash contact areas with soap and water. Remove contaminated clothing. Launder contaminated clothing before reuse. If product is injected into or under the skin, or into any part of the body, regardless of the appearance of the wound or its size, the individual should be evaluated immediately by a physician as a surgical emergency. Even though initial symptoms from high pressure injection may be minimal or absent, early surgical treatment within the first few hours may significantly reduce the ultimate extent of injury.

EYE CONTACT

Flush thoroughly with water. If irritation occurs, get medical assistance.

INGESTION

Seek immediate medical attention. Do not induce vomiting.

NOTE TO PHYSICIAN

If ingested, material may be aspirated into the lungs and cause chemical pneumonitis. Treat appropriately.

PRE-EXISTING MEDICAL CONDITIONS WHICH MAY BE AGGRAVATED BY EXPOSURE

Contains benzene; individuals with pre-existing liver disease may be more susceptible to toxic effects.

SECTION 5 FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

Appropriate Extinguishing Media: Use water fog, foam, dry chemical or carbon dioxide (CO₂) to extinguish flames.

Inappropriate Extinguishing Media: Straight streams of water

FIRE FIGHTING

Fire Fighting Instructions: Evacuate area. If a leak or spill has not ignited, use water spray to disperse the vapours and to protect personnel attempting to stop a leak. Prevent run-off from fire control or dilution from entering streams, sewers or drinking water supply. Fire-fighters should use standard protective equipment and in enclosed spaces, self-contained breathing apparatus (SCBA). Use water spray to cool fire exposed surfaces and to protect personnel.

Unusual Fire Hazards: Extremely Flammable. Vapour is flammable and heavier than air. Vapour may travel across the ground and reach remote ignition sources, causing a flashback fire danger.

Hazardous Combustion Products: Smoke, Fume, Aldehydes, Sulphur oxides, Incomplete combustion products, Oxides of carbon

FLAMMABILITY PROPERTIES

Flash Point [Method]: -40°C (-40°F) [ASTM D-92]

Flammable Limits (Approximate volume % in air): LEL: 1.5 UEL: 7.6

Autoignition Temperature: N/D

SECTION 6 ACCIDENTAL RELEASE MEASURES

NOTIFICATION PROCEDURES

In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

PROTECTIVE MEASURES

Avoid contact with spilled material. Warn or evacuate occupants in surrounding and downwind areas if required, due to toxicity or flammability of the material. See Section 5 for fire fighting information. See the Hazard Identification Section for Significant Hazards. See Section 4 for First Aid Advice. See Section 8 for advice on the minimum requirements for personal protective equipment. Additional protective measures may be necessary, depending on the specific circumstances and/or the expert judgment of the emergency responders.

SPILL MANAGEMENT

Land Spill: Eliminate all ignition sources (no smoking, flares, sparks or flames in immediate area). Stop leak if you can do so without risk. All equipment used when handling the product must be grounded. Do not touch or walk through spilled material. Prevent entry into waterways, sewer, basements or confined areas. A vapour-suppressing foam may be used to reduce vapour. Use clean non-sparking tools to collect absorbed material. Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers. Large Spills: Water spray may reduce vapour, but may not prevent ignition in enclosed spaces.

Water Spill: Eliminate all ignition sources (no smoking, flares, sparks or flames in immediate area). Stop leak if you can do so without risk. Do not confine in area of spill. Advise occupants and shipping in downwind areas of fire and explosion hazard and warn them to stay clear. Allow liquid to evaporate from the surface. Seek the advice of a specialist before using dispersants.

Water spill and land spill recommendations are based on the most likely spill scenario for this material; however, geographic conditions, wind, temperature, (and in the case of a water spill) wave and current direction and speed may greatly influence the appropriate action to be taken. For this reason, local experts should be consulted. Note: Local regulations may prescribe or limit action to be taken.

ENVIRONMENTAL PRECAUTIONS

Large Spills: Dyke far ahead of liquid spill for later recovery and disposal. Prevent entry into waterways, sewers, basements or confined areas.

SECTION 7

HANDLING AND STORAGE

HANDLING

Avoid breathing mists or vapour. Avoid contact with skin. Prevent exposure to ignition sources, for example use non-sparking tools and explosion-proof equipment. Potentially toxic/irritating fumes/vapour may be evolved from heated or agitated material. Do not siphon by mouth. Use only with adequate ventilation. Do not use as a cleaning solvent or other non-motor fuel uses. For use as a motor fuel only. It is dangerous and/or unlawful to put petrol into unapproved containers. Do not fill container while it is in or on a vehicle. Static electricity may ignite vapour and cause fire. Place container on ground when filling and keep nozzle in contact with container. Do not use electronic devices (including but not limited to cellular phones, computers, calculators, pagers or other electronic devices etc) in or around any fuelling operation or storage area unless the devices are certified intrinsically safe by an approved national testing agency and to the safety standards required by national and/or local laws and regulations. Prevent small spills and leakage to avoid slip hazard. Material can accumulate static charges which may cause an electrical spark (ignition source). Use proper bonding and/or ground procedures. However, bonding and grounds may not eliminate the hazard from static accumulation. Consult local applicable standards for guidance. Additional references include American Petroleum Institute 2003 (Protection Against Ignitions Arising out of Static, Lightning and Stray Currents) or National Fire Protection

Agency 77 (Recommended Practice on Static Electricity) or CENELEC CLC/TR 50404 (Electrostatics - Code of practice for the avoidance of hazards due to static electricity).

Static Accumulator: This material is a static accumulator. A liquid is typically considered a nonconductive, static accumulator if its conductivity is below 100 pS/m (100x10E-12 Siemens per meter) and is considered a semiconductive, static accumulator if its conductivity is below 10,000 pS/m. Whether a liquid is nonconductive or semiconductive, the precautions are the same. A number of factors, for example liquid temperature, presence of contaminants, anti-static additives and filtration can greatly influence the conductivity of a liquid.

STORAGE

Ample fire water supply should be available. A fixed sprinkler/deluge system is recommended. The container choice, for example storage vessel, may effect static accumulation and dissipation. Keep container closed. Handle containers with care. Open slowly in order to control possible pressure release. Store in a cool, well-ventilated area. Outside or detached storage preferred. Storage containers should be earthed and bonded. Fixed storage containers, transfer containers and associated equipment should be grounded and bonded to prevent accumulation of static charge.

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Substance Name	Form	Limit/Standard			Note	Source
BENZENE		STEL	2.5 ppm		Skin	ACGIH
BENZENE		TWA	0.5 ppm		Skin	ACGIH
CUMENE		TWA	50 ppm			ACGIH
CYCLOHEXANE		TWA	100 ppm			ACGIH
ETHYL ALCOHOL		STEL	1000 ppm			ACGIH
ETHYL BENZENE		TWA	20 ppm			ACGIH
GASOLINE		STEL	200 ppm			Supplier
GASOLINE		TWA	100 ppm			Supplier
GASOLINE	Vapour.	TWA	300 mg/m ³	100 ppm		Supplier
METHYL-TERT-BUTYL ETHER		TWA	50 ppm			ACGIH
n-Hexane		TWA	50 ppm		Skin	ACGIH
NAPHTHALENE		STEL	15 ppm		Skin	ACGIH
NAPHTHALENE		TWA	10 ppm		Skin	ACGIH
TOLUENE		TWA	20 ppm			ACGIH
XYLENES		STEL	150 ppm			ACGIH
XYLENES		TWA	100 ppm			ACGIH

NOTE: Limits/standards shown for guidance only. Follow applicable regulations.

ENGINEERING CONTROLS

The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Control measures to consider:

Use explosion-proof ventilation equipment to stay below exposure limits.

PERSONAL PROTECTION

Personal protective equipment selections vary based on potential exposure conditions such as applications, handling practices, concentration and ventilation. Information on the selection of protective equipment for use with this material, as provided below, is based upon intended, normal usage.

Respiratory Protection: If engineering controls do not maintain airborne contaminant concentrations at a level which is adequate to protect worker health, an approved respirator may be appropriate. Respirator selection, use, and maintenance must be in accordance with regulatory requirements, if applicable. Types of respirators to be considered for this material include:

Half-face filter respirator

For high airborne concentrations, use an approved supplied-air respirator, operated in positive pressure mode. Supplied air respirators with an escape bottle may be appropriate when oxygen levels are inadequate, gas/vapour warning properties are poor, or if air purifying filter capacity/rating may be exceeded.

Hand Protection: Any specific glove information provided is based on published literature and glove manufacturer data. Glove suitability and breakthrough time will differ depending on the specific use conditions. Contact the glove manufacturer for specific advice on glove selection and breakthrough times for your use conditions. Inspect and replace worn or damaged gloves. The types of gloves to be considered for this material include:

If prolonged or repeated contact is likely, chemical-resistant gloves are recommended. If contact with forearms is likely, wear gauntlet-style gloves.

Eye Protection: If contact is likely, safety glasses with side shields are recommended.

Skin and Body Protection: Any specific clothing information provided is based on published literature or manufacturer data. The types of clothing to be considered for this material include:

If prolonged or repeated contact is likely, chemical, and oil resistant clothing is recommended.

Specific Hygiene Measures: Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practise good housekeeping.

ENVIRONMENTAL CONTROLS

Comply with applicable environmental regulations limiting discharge to air, water and soil. Protect the environment by applying appropriate control measures to prevent or limit emissions.

SECTION 9

PHYSICAL AND CHEMICAL PROPERTIES

Note: Physical and chemical properties are provided for safety, health and environmental considerations only and may not fully represent product specifications. Contact the Supplier for additional information.

GENERAL INFORMATION

Physical State: Liquid
Colour: Clear (May Be Dyed)
Odour: Petroleum/Solvent
Odour Threshold: N/D

IMPORTANT HEALTH, SAFETY, AND ENVIRONMENTAL INFORMATION

Relative Density (at 15 °C): 0.751
Flash Point [Method]: -40°C (-40°F) [ASTM D-92]
Flammable Limits (Approximate volume % in air): LEL: 1.5 UEL: 7.6
Autoignition Temperature: N/D
Boiling Point / Range: 35°C (95°F) - 225°C (437°F)

Vapour Density (Air = 1): 4 at 101 kPa
Vapour Pressure: 45 kPa (337.5 mm Hg) at 20°C - 74 kPa (555 mm Hg) at 20°C
Evaporation Rate (n-butyl acetate = 1): > 10
pH: N/A
Log Pow (n-Octanol/Water Partition Coefficient): > 3
Solubility in Water: Appreciable
Viscosity: <1 cSt (1 mm²/sec) at 40°C | 0.8 cSt (0.8 mm²/sec) at 20°C
Oxidizing Properties: See Hazards Identification Section.

OTHER INFORMATION

Freezing Point: N/D
Melting Point: N/A
Pour Point: < -60°C (-76°F)

SECTION 10 STABILITY AND REACTIVITY

STABILITY: Material is stable under normal conditions.
CONDITIONS TO AVOID: Avoid heat, sparks, open flames and other ignition sources.
MATERIALS TO AVOID: Halogens, Strong Acids, Alkalies, Strong oxidizers
HAZARDOUS DECOMPOSITION PRODUCTS: Material does not decompose at ambient temperatures.
HAZARDOUS POLYMERIZATION: Will not occur.

SECTION 11 TOXICOLOGICAL INFORMATION

ACUTE TOXICITY

<u>Route of Exposure</u>	<u>Conclusion / Remarks</u>
Inhalation	
Toxicity (Rat): LC50 > 5000 mg/m ³	Minimally Toxic. Based on test data for structurally similar materials.
Irritation: No end point data.	Elevated temperatures or mechanical action may form vapours, mist, or fumes which may be irritating to the eyes, nose, throat, or lungs. Based on assessment of the components.
Ingestion	
Toxicity (Rat): LD50 > 2000 mg/kg	Minimally Toxic. Based on test data for structurally similar materials.
Skin	
Toxicity (Rabbit): LD50 > 2000 mg/kg	Minimally Toxic. Based on test data for structurally similar materials.
Irritation: No end point data.	Mildly irritating to skin with prolonged exposure. Based on test data for structurally similar materials.
Eye	
Irritation: Data available.	May cause mild, short-lasting discomfort to eyes. Based on test data for structurally similar materials.

CHRONIC/OTHER EFFECTS
 For the product itself:

Laboratory animal studies have shown that prolonged and repeated inhalation exposure to light hydrocarbon vapours in the same boiling range as this product can produce adverse kidney effects in male rats. However, these effects were not observed in similar studies with female rats, male and female mice, or in limited studies with other animal species. Additionally, in a number of human studies, there was no clinical evidence of such effects at normal occupational levels. In 1991, The U.S. EPA determined that the male rat kidney is not useful for assessing human risk. Vapour concentrations above recommended exposure levels are irritating to the eyes and the respiratory tract, may cause headaches and dizziness, are anaesthetic and may have other central nervous system effects. Small amounts of liquid aspirated into the lungs during ingestion or from vomiting may cause chemical pneumonitis or pulmonary edema.

Contains:

BENZENE: Caused cancer (leukemia), damage to the blood-producing system, and serious blood disorders from prolonged, high exposure based on human epidemiology studies. Caused genetic effects and effects on the immune system in laboratory animal and some human studies. Caused toxicity to the fetus in laboratory animal studies.

CUMENE: Repeated inhalation exposure of cumene vapour produced damage in the kidney of male rats only. These effects are believed to be species specific and are not relevant to humans. **ETHANOL:** Prolonged or repeated exposure to high concentrations of ethanol vapour or overexposure by ingestion may produce adverse effects to brain, kidney, liver, and reproductive organs, birth defects in offspring, and developmental toxicity in offspring. **GASOLINE UNLEADED:** Carcinogenic in animal tests. Chronic inhalation studies resulted in liver tumours in female mice and kidney tumours in male rats. Neither result considered significant for human health risk assessment by the United States EPA and others. Did not cause mutations in-vitro or in-vivo. Negative in inhalation developmental studies and reproductive tox studies. Inhalation of high concentrations in animals resulted in reversible central nervous system depression, but no persistent toxic effect on the nervous system. Non-sensitizing in test animals. Caused nerve damage in humans from abusive use (sniffing). **METHYL TERTIARY BUTYL ETHER (MTBE):** Carcinogenic in animal tests. Inhalation exposure to high concentrations resulted in higher than expected mortality in male mice due to urinary tract obstructions and female mice displayed benign liver tumours. Inhalation exposure to high concentrations resulted in higher than expected mortality in male rats due to progressive kidney damage as well as increased benign and malignant kidney tumours, and benign testicular tumours. Did not cause mutations in-vitro or in-vivo. Rabbits exposed to high vapour concentrations did not have any offspring with adverse developmental effects. Mice exposed to high vapour concentrations (maternally toxic) had offspring with embryo/fetal toxicity and birth defects. Rats exposed to high vapour concentrations did not display any treatment-related effects in a two generation reproduction study. The significance of the animal findings at high exposures are not believed to be directly related to potential human health hazards in the workplace. **NAPHTHALENE:** Exposure to high concentrations of naphthalene may cause destruction of red blood cells, anemia, and cataracts. Naphthalene caused cancer in laboratory animal studies, but the relevance of these findings to humans is uncertain.

N-HEXANE: Prolonged and/or repeated exposures to n-Hexane can cause progressive and potentially irreversible damage to the peripheral nervous system (e.g. fingers, feet, arms, legs, etc.). Simultaneous exposure to Methyl Ethyl Ketone (MEK) or Methyl Isobutyl Ketone (MIBK) and n-Hexane can potentiate the risk of adverse effects from n-Hexane on the peripheral nervous system. n-Hexane has been shown to cause testicular damage at high doses in male rats. The relevance of this effect for humans is unknown. **TOLUENE :** Concentrated, prolonged or deliberate inhalation may cause brain and nervous system damage. Prolonged and repeated exposure of pregnant animals (> 1500 ppm) have been reported to cause adverse fetal developmental effects. **ETHYLBENZENE:** Caused cancer in laboratory animal studies. The relevance of these findings to humans is uncertain.

XYLENES: High exposures to xylenes in some animal studies have been reported to cause health effects on the developing embryo/fetus. These effects were often at levels toxic to the mother. The significance of these findings to humans has not been determined.

Additional information is available by request.

CMR Status:

Chemical Name	CAS Number	List Citations
BENZENE	71-43-2	1, 4, 5
CUMENE	98-82-8	4
CYCLOHEXANE	110-82-7	4
ETHYL ALCOHOL	64-17-5	4
ETHYL BENZENE	100-41-4	3, 4
GASOLINE	86290-81-5	3, 4
METHYL-TERT-BUTYL ETHER	1634-04-4	4
n-Hexane	110-54-3	4
NAPHTHALENE	91-20-3	3, 4
TOLUENE	108-88-3	4
XYLENES	1330-20-7	4

--REGULATORY LISTS SEARCHED--

1 = IARC 1
 2 = IARC 2A

3 = IARC 2B
 4 = ACGIH ALL

5 = ACGIH A1
 6 = ACGIH A2

SECTION 12 ECOLOGICAL INFORMATION

The information given is based on data available for the material, the components of the material, and similar materials.

ECOTOXICITY

Material -- Expected to be toxic to aquatic organisms. May cause long-term adverse effects in the aquatic environment.

MOBILITY

More volatile component -- Highly volatile, will partition rapidly to air. Not expected to partition to sediment and wastewater solids.

Less volatile component -- Low solubility and floats and is expected to migrate from water to the land. Expected to partition to sediment and wastewater solids.

PERSISTENCE AND DEGRADABILITY

Biodegradation:

Majority of components -- Expected to be inherently biodegradable

Atmospheric Oxidation:

More volatile component -- Expected to degrade rapidly in air

BIOACCUMULATION POTENTIAL

Majority of components -- Has the potential to bioaccumulate, however metabolism or physical properties may reduce the bioconcentration or limit bioavailability.

SECTION 13 DISPOSAL CONSIDERATIONS

Disposal recommendations based on material as supplied. Disposal must be in accordance with current applicable laws and regulations, and material characteristics at time of disposal.

DISPOSAL RECOMMENDATIONS

Product is suitable for burning in an enclosed controlled burner for fuel value or disposal by supervised incineration at very high temperatures to prevent formation of undesirable combustion products.

REGULATORY DISPOSAL INFORMATION

Empty Container Warning Empty Container Warning (where applicable): Empty containers may contain residue and can be dangerous. Do not attempt to refill or clean containers without proper instructions. Empty drums should be completely drained and safely stored until appropriately reconditioned or disposed. Empty containers should be taken for recycling, recovery, or disposal through suitably qualified or licensed contractor and in accordance with governmental regulations. DO NOT PRESSURISE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION. THEY MAY EXPLODE AND CAUSE INJURY OR DEATH.

SECTION 14	TRANSPORT INFORMATION
-------------------	------------------------------

LAND (TDG)

Proper Shipping Name: GASOLINE
Hazard Class & Division: 3
UN Number: 1203
Packing Group: II
Marine Pollutant: Yes
Special Provisions: 17

Footnote: Marine Pollutant designation is applicable only if shipped over water.

LAND (DOT)

Proper Shipping Name: GASOLINE
Hazard Class & Division: 3
ID Number: 1203
Packing Group: II
ERG Number: 128
Label(s): 3
Transport Document Name: UN1203, GASOLINE, 3, PG II

SEA (IMDG)

Proper Shipping Name: MOTOR SPIRIT or GASOLINE or PETROL
Hazard Class & Division: 3
EMS Number: F-E, S-E
UN Number: 1203
Packing Group: II
Label(s): 3
Transport Document Name: UN1203, MOTOR SPIRIT or GASOLINE or PETROL, 3, PG II, (-40°C c.c.)

AIR (IATA)

Proper Shipping Name: MOTOR SPIRIT or GASOLINE or PETROL
Hazard Class & Division: 3
UN Number: 1203
Packing Group: II
Label(s) / Mark(s): 3
Transport Document Name: UN1203, GASOLINE, 3, PG II

SECTION 15 REGULATORY INFORMATION

WHMIS Classification: Class B, Division 2: Flammable Liquids Class D, Division 2, Subdivision A: Very Toxic Material

This product has been classified in accordance with hazard criteria of the Controlled Products Regulations and the (M)SDS contains all the information required by the Controlled Products Regulations.

CEPA: All components of this material are either on the Canadian Domestic Substances List (DSL), exempt, or have been notified under CEPA.

Complies with the following national/regional chemical inventory requirements: AICS, DSL, EINECS, ENCS, KECI, PICCS, TSCA

The Following Ingredients are Cited on the Lists Below:

Chemical Name	CAS Number	List Citations
BENZENE	71-43-2	6
CUMENE	98-82-8	6
CYCLOHEXANE	110-82-7	6
ETHYL BENZENE	100-41-4	6
METHYL-TERT-BUTYL ETHER	1634-04-4	6
n-Hexane	110-54-3	6
NAPHTHALENE	91-20-3	6
TOLUENE	108-88-3	6
XYLENES	1330-20-7	6

--REGULATORY LISTS SEARCHED--

1 = TSCA 4
 2 = TSCA 5a2

3 = TSCA 5e
 4 = TSCA 6

5 = TSCA 12b
 6 = NPRI

SECTION 16 OTHER INFORMATION

N/D = Not determined, N/A = Not applicable

THIS SAFETY DATA SHEET CONTAINS THE FOLLOWING REVISIONS:

- Revision Changes:
 Section 06: Protective Measures was modified.
 Section 09: Phys/Chem Properties Note was modified.
 Section 09: Boiling Point C(F) was modified.
 Section 08: Comply with applicable regulations phrase was modified.
 Section 09: Vapour Pressure was modified.
 Section 07: Handling and Storage-Storage Phrases was modified.
 Section 09: Relative Density - Header was modified.

Section 09: Flash Point C(F) was modified.
Section 09 Viscosity was modified.
Section 09 Viscosity was modified.
Section 04: First Aid Pre-existing Medical Conditions was modified.
Section 15: National Chemical Inventory Listing - Header was modified.
Section 16: Synonyms was modified.
Composition: Component table was modified.
Composition: Component table was modified.
Section 08: Exposure Limits Table was modified.
Section 15: Canadian List Citations Table was modified.
Section 01: Company Contact Methods Sorted by Priority was modified.

SYNONYMS: GASOLINE REGULAR UNLEADED RUL87 LDCA WITH ETHANOL, GASOLINE REGULAR UNLEADED RUL87 DCA DYED WITH ETHANOL, GASOLINE MIDGRADE UNLEADED MUL89 LDCA WITH ETHANOL, GASOLINE REGULAR UNLEADED RUL87 LDCA DYED WITH ETHANOL, GASOLINE MIDGRADE UNLEADED MUL89 DCA WITH ETHANOL, GASOLINE REGULAR UNLEADED RUL87 WITH ETHANOL, GASOLINE REGULAR UNLEADED RUL87 DCA WITH ETHANOL, OXYGENATED UNLEADED AUTOMOTIVE GASOLINE CONTAINING ETHANOL, ESSO EXTRA MIDGRADE GASOLINE WITH ETHANOL, ESSO MIDGRADE GASOLINE WITH ETHANOL, ESSO PREMIUM GASOLINE WITH ETHANOL, ESSO REGULAR GASOLINE WITH ETHANOL, EXXON MIDGRADE GASOLINE WITH ETHANOL, EXXON PREMIUM GASOLINE WITH ETHANOL, EXXON REGULAR GASOLINE WITH ETHANOL, GASOLINE REGULAR UNLEADED RUL87 DYED WITH ETHANOL

PRECAUTIONARY LABEL TEXT:

WHMIS Classification: Class B, Division 2: Flammable Liquids Class D, Division 2, Subdivision A: Very Toxic Material

HEALTH HAZARDS

May cause cancer. Repeated exposure may cause skin dryness or cracking. If swallowed, may be aspirated and cause lung damage. May cause central nervous system depression.

Target Organs: Blood and/or blood-forming organs |

PHYSICAL HAZARDS

FLAMMABLE. Material can accumulate static charges which may cause an ignition. Material can release vapours that readily form flammable mixtures. Vapour accumulation could flash and/or explode if ignited.

PRECAUTIONS

Avoid breathing mists or vapour. Avoid contact with skin. Prevent exposure to ignition sources, for example use non-sparking tools and explosion-proof equipment. Potentially toxic/irritating fumes/vapour may be evolved from heated or agitated material. Do not siphon by mouth. Use only with adequate ventilation. Use proper bonding and/or earthing procedures. However, bonding and earthing may not eliminate the hazard from static accumulation.

FIRST AID

Inhalation: Remove from further exposure. For those providing assistance, avoid exposure to yourself or others. Use adequate respiratory protection. If respiratory irritation, dizziness, nausea, or unconsciousness occurs, seek immediate medical assistance. If breathing has stopped, assist ventilation with a mechanical device or use mouth-to-mouth resuscitation.

Eye: Flush thoroughly with water. If irritation occurs, get medical assistance.

Oral: Seek immediate medical attention. Do not induce vomiting.

Skin: Wash contact areas with soap and water. Remove contaminated clothing. Launder contaminated clothing

before reuse. If product is injected into or under the skin, or into any part of the body, regardless of the appearance of the wound or its size, the individual should be evaluated immediately by a physician as a surgical emergency. Even though initial symptoms from high pressure injection may be minimal or absent, early surgical treatment within the first few hours may significantly reduce the ultimate extent of injury.

FIRE FIGHTING MEDIA

Use water fog, foam, dry chemical or carbon dioxide (CO₂) to extinguish flames.

SPILL/LEAK

Land Spill: Eliminate all ignition sources (no smoking, flares, sparks or flames in immediate area). Stop leak if you can do so without risk. Prevent entry into waterways, sewer, basements or confined areas. A vapour-suppressing foam may be used to reduce vapour. Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers.

Water Spill: Eliminate all ignition sources (no smoking, flares, sparks or flames in immediate area). Stop leak if you can do so without risk. Do not confine in area of spill. Advise occupants and shipping in downwind areas of fire and explosion hazard and warn them to stay clear. Allow liquid to evaporate from the surface. Seek the advice of a specialist before using dispersants.

The information and recommendations contained herein are, to the best of Imperial Oil's knowledge and belief, accurate and reliable as of the date issued. Imperial Oil assumes no responsibility for accuracy of information unless the document is the most current available from an official Imperial Oil distribution system. The information and recommendations are offered for the user's consideration and examination, and it is the user's responsibility to satisfy itself that they are suitable and complete for its particular use. If buyer repackages this product, legal counsel should be consulted to insure proper health, safety and other necessary information is included on the container. Appropriate warnings and safe-handling procedures should be provided to handlers and users. Alteration of this document is strictly prohibited. Except to the extent required by law, republication or retransmission of this document, in whole or in part, is not permitted.

DGN: 5010466 (1012958)

Copyright 2002 Imperial Oil Limited, All rights reserved

Prepared by: Imperial Oil Limited, IH and Product Safety



No. Co. Equity

MATERIAL SAFETY DATA SHEET

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

CHS Inc.
P.O. Box 64089
Mail station 525
St. Paul, MN 55164-0089

Transportation Emergency (CHEMTREC): 1-800-424-9300
Technical Information: 1-651-355-8443
MSDS Information: 1-651-355-8438

PRODUCT NAME: Gasohol; Unleaded Gasoline with Ethanol
COMMON NAME: Gasohol; Ethanol Blends
CHEMICAL NAME: Light Petroleum Distillate

MSDS: 0164-M9A0 - Rev. E (03/10/06)
CHEMICAL FORMULA: Mixture
CHEMICAL FAMILY: Mixed Petroleum Hydrocarbon

Section 2 - COMPOSITION AND INFORMATION ON INGREDIENTS

INGREDIENTS	PERCENTAGES (by weight)	PEL (OSHA)	TLV (ACGIH)	CAS #
<u>Product</u>				
Gasoline (Mixture)	100	300 ppm TWA 500 ppm STEL	300 ppm TWA 500 ppm STEL	8006-61-9
<u>Ingredients</u>				
Toluene	< 20	100 ppm TWA 150 ppm STEL	50 ppm TWA	108-88-3
Xylene Isomers	< 20	100 ppm TWA 150 ppm STEL	100 ppm TWA 150 ppm STEL	1330-20-7
Ethyl Alcohol (Ethanol)	< 20	1000 ppm TWA	1000 ppm TWA	64-17-5
Benzene	< 6	1 ppm TWA 5 ppm STEL	0.5 ppm TWA 2.5 ppm STEL	71-43-2
1,2,4-Trimethylbenzene	< 5	25 ppm TWA	25 ppm TWA	95-63-6
Ethyl Benzene	< 3	100 ppm TWA 125 ppm STEL	100 ppm TWA 125 ppm STEL	100-41-4

(TWA) - Time Weighted Average is the employee's average airborne exposure in any 8-hour work shift of a 40-hour work week which shall not be exceeded.
(STEL) - Short Term Exposure Limit is the employee's 15-minute time weighted average exposure which shall not be exceeded at any time during a work day unless another time limit is specified.

Section 3 - HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

Reddish golden brown liquid with gasoline odor - HIGHLY FLAMMABLE LIQUID.
DANGER! Contains Benzene. Cancer Hazard. Can cause kidney, liver and blood disorders.

OSHA HAZARD CLASS

Based on OSHA definitions, the following ingredients in this product are hazardous. The OSHA physical and health hazard categories are shown below. Note: Cenex has not conducted specific toxicity tests on this product. Our hazard evaluation is based on information from similar products, the ingredients, technical literature, and/or professional experience.

Gasoline - Flammable, toxic, irritant, target organ (CNS)
 Toluene - Flammable, toxic, irritant, target organ (CNS)
 Xylene - Flammable, toxic, irritant
 Ethyl Alcohol - Flammable, toxic, irritant, target organ (reproductive, CNS, skin)
 Benzene - Flammable, irritant, carcinogen, target organ (kidney, liver, blood)
 1,2,4-Trimethylbenzene - Flammable, toxic, irritant, target organ (CNS, blood)
 Ethylbenzene - Flammable, toxic, irritant

POTENTIAL HEALTH EFFECTS

ROUTES OF ENTRY: Inhalation, Dermal, Ingestion.

ACUTE EFFECTS OF OVER EXPOSURE:

Eyes - Slight to moderate eye irritation.

Skin - Moderately irritating; causes redness, drying of skin.

Inhalation - Irritating to mucous membranes and respiratory tract. Causes dizziness, irritation of eyes, nose and throat, signs of intoxications. Can act as a simple asphyxiant.

Ingestion - Burning of the throat and stomach, loss of consciousness, convulsions, cyanosis, congestion and capillary hemorrhaging of the lungs and internal organs. Possible pneumonia (if vomited), loss of consciousness, and death.

CHRONIC EFFECTS OF OVER EXPOSURE: Suspect carcinogen from long term exposure studies on laboratory animals. Recent studies with laboratory animals have shown that gasoline vapors caused kidney damage and kidney cancer in rats and liver cancer in mice.

Mouse skin painting studies have shown that petroleum middle distillates (boiling range of 100-700°F) can cause skin cancer when repeatedly applied and never washed from the animal's skin. The relative significance of this to the skin and the resulting skin effects (irritation, cell damage, etc.) may play a role in the tumorigenic response. Studies have shown that washing the animal's skin with soap and water between treatments greatly reduces the carcinogenic effect of some petroleum oils.

A few studies have indicated that workers exposed many years to high concentrations of benzene have a slightly higher incidence of leukemia. Benzene can also be toxic to the blood and blood-forming tissues. For additional information on employee monitoring, information and training, medical surveillance, methods of compliance, etc., refer to the OSHA benzene standard, CFR 1910.1028.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: May aggravate pre-existing dermatitis, respiratory illness, or other conditions which have the same symptoms or effects as stated above.

CARCINOGENICITY:

Unleaded Gasoline - NTP:	<u>No</u>	IARC:	<u>No</u>	OSHA:	<u>No</u>
Benzene -	NTP: <u>Yes</u>	IARC:	<u>Yes</u>	OSHA:	<u>Yes</u>

Section 4 - FIRST AID MEASURES

EMERGENCY AND FIRST AID PROCEDURES:

Eye Contact - If material comes in contact with the eyes, immediately wash the eyes with large amounts of water, occasionally lifting the lower and upper lids until medical attention can be obtained.

Skin Contact - Remove contaminated clothing. Wash affected areas with soap and water. If irritation or redness develops, seek medical attention.

Inhalation - Move person away from source of exposure and into fresh air. If symptoms persist, seek immediate medical attention. Apply artificial respiration or cardiopulmonary resuscitation if not breathing. Get medical attention.

Ingestion - Never give anything by mouth to an unconscious person. Do **not** induce vomiting. Aspiration of material into the lungs due to vomiting can cause chemical pneumonitis which can be fatal. If spontaneous vomiting occurs, keep head below hips to prevent aspiration of liquid into lungs and monitor for breathing difficulty. Seek medical attention immediately. Keep victim warm and quiet.

Section 5 - FIRE - FIGHTING MEASURES

FLASH POINT: -40°F (TCC)

AUTO IGNITION TEMP: 495-850°F

FLAMMABLE LIMITS IN AIR
% BY VOLUME

LOWER	UPPER
1.4	7.6

EXTINGUISHING MEDIA: Dry Chemical, Foam, Carbon Dioxide (CO₂), Water (fog pattern).

SPECIAL FIRE FIGHTING PROCEDURES: Water may be ineffective on flames, but should be used to keep fire-exposed containers cool. Large fires, such as tank fires, should be fought with caution. If possible, pump the contents from the tank and keep adjoining structures cool and protect personnel. Avoid spreading burning liquid with water used for cooling purposes. Do not flush down public sewers. The use of a self-contained breathing apparatus and protective clothing is recommended for fire fighters. Avoid inhalation of vapors.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Highly volatile material. Flowing gasoline can be ignited by self-generated static electricity; containers should be bonded and grounded. Vapors may travel along the ground to a source of ignition (pilot light, heater, electric motor) some distance away. Containers, drums (even empty) can explode when heat (welding, cutting, etc.) is applied.

HAZARD RATINGS:	NFPA 704:	Health- <u>1</u>	Fire- <u>3</u>	Reactivity- <u>0</u>
	HMIS:	Health- <u>2</u>	Fire- <u>4</u>	Reactivity- <u>0</u>

Section 6 - ACCIDENTAL RELEASE MEASURES

STEPS TO TAKE IF MATERIAL IS RELEASED OR SPILLED: Notify emergency response personnel as appropriate. If facility or operation has an "Oil or Hazardous Substance Contingency Plan", "Spill Prevention Control & Countermeasures (SPCC) Plan" or equivalent, activate its procedures. REMOVE ALL SOURCES OF IGNITION. Keep unnecessary people away; isolate hazard area and deny entry. Contain spill if possible. Small spills can be removed with inert absorbent. Dike area of large spill to prevent run-off to sewers, streams, etc. Ventilate area. Avoid breathing vapors. Use appropriate personal protective equipment during clean up. Contact fire authorities and notify appropriate Federal, State, and Local agencies.

Section 7 - HANDLING AND STORAGE

HANDLING AND STORING: Transport, handle and store in accordance with OSHA Regulation 29 CFR 1910.106, and applicable D.O.T. Regulations. Store in tightly closed containers in a dry cool place, away from sources of heat or ignition. Ground and bond all transfer and storage equipment and equip with self-closing valves, pressure vacuum bungs and flame arrestors. **Caution:** Misuse of empty containers can be hazardous. Empty containers can be hazardous if used to store toxic, flammable, or reactive materials. Cutting, welding or other of empty containers might cause fire, explosion or toxic fumes from residues. Do not pressurize or expose to open flame, heat, sparks or other sources of ignition. Do not siphon gasoline by mouth.

WARNING: Danger! Contains Benzene. Cancer Hazard. Can cause kidney, liver and blood disorders. **Other:** Do not siphon gasoline by mouth. May cause irritation to eyes, skin and respiratory system. Avoid liquid, mist and vapor contact. Harmful or fatal if swallowed. Aspiration hazard, can enter lungs and cause damage. May cause irritation or be harmful if inhaled or absorbed through the skin. Flammable Liquid. Vapors may explode.

Section 8 - EXPOSURE CONTROL - PERSONAL PROTECTION

ENGINEERING CONTROLS: Provide adequate ventilation to keep vapors below permissible concentrations.

RESPIRATORY EQUIPMENT: Use appropriate NIOSH-approved respiratory protection where atmospheric concentrations may exceed acceptable exposure limits. Self-contained breathing apparatus or supplied air respiratory protection required for entry into tanks, vessels, or other confined spaced containing gasoline.

EYE PROTECTION: Chemical type goggles or face shield where contact with liquid or mist may occur.

PROTECTIVE CLOTHING: Wear impervious clothing and gloves when contact with skin may occur.

OTHER (SAFETY SHOWERS, EYE WASH STATIONS, ETC.): Emergency eye wash station and safety shower where operations and exposure warrant. Loading, unloading, tank gauging, etc., remain upwind.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: Reddish golden brown liquid
BOILING POINT: 760 mmHg @ 80°F
VAPOR PRESSURE: 400 mmHg @ 68°F
SOLUBLE IN WATER: Negligible
pH: N/D

ODOR: Gasoline odor (odor threshold approximately 10 ppm).
SPECIFIC GRAVITY (water=1): .72
VAPOR DENSITY (air=1): 4
EVAPORATION RATE (ether=1): Slower

Section 10 - STABILITY AND REACTIVITY

STABILITY

STABLE (At room temperature and pressure. See handling and storage section)
UNSTABLE

INCOMPATIBILITY -

CONDITIONS TO AVOID: Heat, sparks, flame, build-up of static electricity, and other sources of ignition should be avoided.

MATERIALS TO AVOID: Strong oxidizing agents, halogens, strong acids, and alkalis.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide, carbon dioxide, and hydrocarbons.

HAZARDOUS POLYMERIZATION: Has not been reported to occur under normal temperatures and pressures.

Section 11 - TOXICOLOGY INFORMATION

Note: CHS has not conducted specific toxicity tests on this product.

Section 12 - ECOLOGICAL INFORMATION

Note: CHS has not conducted specific ecological tests on this product.

Section 13 - DISPOSAL CONSIDERATION

WASTE DISPOSAL PROCEDURES: Recycle as much of the recoverable product as possible. Do not flush to drain or storm sewer or otherwise release to the environment. Dispose of non-recyclable material as a RCRA hazardous waste, complying with federal, state and local regulations. Note: Re-evaluation of this product may be required by the user at the time of disposal, since the product uses, transformations, mixtures and processes may change classification to non-hazardous or hazardous for reasons other than, or in addition to ignitable.

Section 14 - TRANSPORTATION

DOT PROPER SHIPPING NAME: Gasoline*
DOT HAZARD CLASS: Flammable Liquid*
DOT IDENTIFICATION NUMBER: UN 1203
DOT EMER. RESPONSE GUIDE NO.: 128
 (Formerly #27)

*EFFECTIVE 10/1/93 DOT's HM-181 changes how materials are classified. Proper Shipping Name-Gasoline; Hazard Class-3; UN/NA Identification #- UN 1203, Packing Group II; Placard-FLAMMABLE



MATERIAL SAFETY DATA SHEET

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

CHS Inc.
P.O. Box 64089
Mail station 525
St. Paul, MN 55164-0089

Transportation Emergency (CHEMTREC): 1-800-424-9300
Technical Information: 1-651-355-8443
MSDS Information: 1-651-355-8438

PRODUCT NAME: No. 2 Ultra Low Sulfur Diesel Fuel / Distillate

MSDS: 0201-M1A0.3 - Rev. B (02/16/07)

COMMON NAME: #2 Diesel Fuel, #2 Distillate, Fuel Oil
Fieldmaster XL Diesel Fuel, Roadmaster XL Diesel Fuel

CHEMICAL FORMULA: Mixture

CHEMICAL NAME: Petroleum Distillate

CHEMICAL FAMILY: A mixture of paraffinic, olefinic, naphthenic and aromatic hydrocarbons.

Section 2 - COMPOSITION AND INFORMATION ON INGREDIENTS

INGREDIENTS	PERCENTAGES (by weight)	PEL (OSHA)	TLV (ACGIH)	CAS #
Diesel Fuel	99-100%	N/D	N/D	68476-34-6
Sulfur	(15 ppm)	N/D	N/D	7704-34-9

Other components: 1,2,4-Trimethylbenzene (95-52-4, <0.6%), Biphenyl (92-52-4, <0.6%), Xylene (1330-20-7, <0.2%)
Naphthalene (91-20-3, <0.2%)

(TWA) - Time Weighted Average is the employee's average airborne exposure in any 8-hour work shift of a 40-hour work week which shall not be exceeded.
(STEL) - Short Term Exposure Limit is the employee's 15-minute time weighted average exposure which shall not be exceeded at any time during a work day unless another time limit is specified.

Section 3 - HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

A clear, to yellow or red liquid with a hydrocarbon odor. **Danger! Harmful or Fatal if Swallowed**

OSHA Hazard Classes

Based on OSHA definitions, the following ingredients in this product are hazardous. The OSHA physical and health Hazard categories are shown below. Note: CHS has not conducted specific toxicity tests on this product.

Our hazard evaluation is based on information from similar ingredients, technical literature, and/or professional experience.

Diesel Fuel - Combustible, toxic (moderate), target organ (Skin, Central Nervous System)

POTENTIAL HEALTH EFFECTS

ROUTES OF ENTRY: (Eye Contact, Dermal, Inhalation, Ingestion.)

ACUTE EFFECTS OF OVER EXPOSURE:

Eyes - Contact with eyes may cause irritation.

Skin - Contact with skin may cause irritation.

Inhalation - May cause respiratory tract irritation. High levels may cause headache, dizziness, nausea, vomiting in-coordination and unconsciousness.

Ingestion - May cause nausea, vomiting, cramping, diarrhea, and central nervous system depression. Pulmonary irritation from exhaling solvent and delayed signs of liver and kidney damage may also occur.

CHRONIC EFFECTS OF OVER EXPOSURE: Dermatitis from chronic exposure. Products of similar composition (boiling ranges of 100-700; naphtha, jet fuel, diesel fuel, etc.) were tested on laboratory animals by repeatedly applying and never washing from the animal's skin. Weak to moderately positive results were found in mouse skin cancer studies, mixed and inconsistent results were found in mutagenicity studies, and negative results were found in rate teratology studies. A few studies have shown that washing the animal's skin with soap and water between treatment greatly reduces the carcinogenic skin cancer in humans. This material is not listed as a carcinogen by International Association for Research on Cancer, or Occupational Safety and Health Administration.

Prolonged exposure from inhalation of vapors may cause dizziness, weakness, weight loss, anemia, nervousness, pains in the limbs, peripheral numbness, and paresthesia. Degenerative changes in the liver and kidneys may occur after prolonged exposure to high concentrations.

The National Institute for Occupational Safety and Health (NIOSH), based on findings on carcinogenic and tumorigenic responses of mice and rats exposed to whole diesel exhaust, recommends that diesel exhaust be regarded as a "potential occupational carcinogen".

Medical Conditions Aggravated By Exposure: Conditions which have the same symptoms or effects as stated above.

Carcinogenic Potential: this material may contain ethylbenzene and naphthalene at concentrations above 0.1%. IARC has identified ethylbenzene and naphthalene as possibly carcinogenic to humans (group 2) based on laboratory animal studies. NTP has determined that exposure to diesel exhaust particulates, a complex mixture of combustion products of diesel fuel, is reasonably anticipated to be a human carcinogen.

Section 4 - FIRST AID MEASURES

EMERGENCY AND FIRST AID PROCEDURES:

Eye Contact - If material comes in contact with the eyes, immediately wash the eyes with large amounts of water for fifteen minutes, occasionally lifting the lower and upper lids. Get medical attention.

Skin Contact - If the material comes in contact with the skin, wash the contaminated skin with soap and water promptly. If the material penetrates through clothing, remove the clothing and wash the skin with soap and water promptly. If irritation persists after washing, get medical attention immediately.

Inhalation - If person breathes in large amounts of material, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the person warm and at rest. Get medical attention as soon as possible.

Ingestion - If material has been swallowed, do not induce vomiting. Get medical attention immediately.

Section 5 - FIRE - FIGHTING MEASURES

FLASH POINT: >125°F (>52°C) (PMCC)

AUTO IGNITION TEMP: >494°F

FLAMMABLE LIMITS IN AIR
% BY VOLUME

LOWER
0.6

UPPER
7.5

EXTINGUISHING MEDIA: Use water spray to cool fire exposed surfaces and to protect personnel. Use foam, dry chemical or water spray (fog) to extinguish fire.

SPECIAL FIRE FIGHTING PROCEDURES: Water may be ineffective on flames, but should be used to keep fire-exposed containers cool. Water or foam sprayed into container or hot burning product could cause frothing and endanger fire fighters. Large fires, such as tank fires, should be fought with caution. If possible, pump the contents from the tank and keep adjoining structures cool with water. Avoid spreading burning liquid with water used for cooling purposes. Do not flush down public sewers. Avoid inhalation of vapors. Fire fighters should wear self-contained breathing apparatus. Combustion may produce CO, CO₂, oxides of nitrogen, oxides of sulfur, and reactive hydrocarbons.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Vapors are heavier than air and may travel along the ground to a source of ignition (pilot light, heater, electric motor) some distance away. Containers, drums (even empty) can explode when heat (welding, cutting, etc.) is applied.

HAZARD RATINGS: NFPA 704: Health- 0 Fire- 2 Reactivity- 0
 HMIS: Health- 1 Fire- 2 Reactivity- 0

Section 6 - ACCIDENTAL RELEASE MEASURES

STEPS TO TAKE IF MATERIAL IS RELEASED OR SPILLED: Remove all sources of ignition. Notify emergency response personnel as appropriate. If facility or operations has an "Oil or Hazardous Substance Contingency Plan", "Spill Prevention Control & Countermeasures (SPCC) Plan" or equivalent, activate its procedures. Prohibit persons not wearing protective equipment from entering the area. Stop leak at source, contain spill to prevent spreading. Small spills can be removed with inert absorbent. Dike area of large spill to prevent runoff to sewers, streams, etc. Ventilate area. Avoid breathing vapors.

Section 7 - HANDLING AND STORAGE

HANDLING AND STORING: Transport, handle and store in accordance with OSHA Regulations 29 CFR 1910.106, and applicable D.O.T. regulation. Caution: Misuse of empty containers can be hazardous. Empty containers can be hazardous since emptied containers retain product residue (vapor, liquid, and/or solid). Cutting or welding empty containers might cause fire, explosion or toxic fumes from residues.

Section 8 - EXPOSURE CONTROL - PERSONAL PROTECTION

ENGINEERING CONTROLS: Ventilation requirements: Provide adequate local or dilution ventilation to keep vapors below permissible concentrations.

RESPIRATORY EQUIPMENT: Personnel should never enter areas of high concentrations without proper respiratory protection. If exposure limits for product or components are exceeded, NIOSH-approved respiratory protection equipment should be worn. Proper selection of respirators should be determined by adequately trained personnel, based on the contaminants, the degree of potential exposure and published respiratory protection factors. Self-contained breathing apparatus or supplied air respiratory protection required for entry into tanks, vessels, or other confined spaces containing #2 Distillate Fuel.

EYE PROTECTION: Chemical goggles or face shield where contact with liquid or mist may occur.

PROTECTIVE CLOTHING: Impervious clothing and gloves when contact with skin may occur.

OTHER (SAFETY SHOWERS, EYE WASH STATIONS, ETC.): Water should be available for flushing and washing when exposure exists. Launder soiled clothes. Discard shoes or other leather articles saturated with the material.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: clear, yellow to red liquid

ODOR: Mild hydrocarbon odor

BOILING POINT: 309°F - 700°F

SPECIFIC GRAVITY (water=1): 0.8400 - 0.9000

VAPOR PRESSURE: <2.6 mm Hg @ 122° F

VAPOR DENSITY (air=1): >4

SOLUBLE IN WATER: Insoluble

EVAPORATION RATE (ether=1): slower

pH: N/D

Section 10 - STABILITY AND REACTIVITY

STABILITY:

 STABLE (At room temperature and pressure. See handling and storage section)

 UNSTABLE
INCOMPATIBILITY -
CONDITIONS TO AVOID: Heat, flame, static electricity and other ignition sources.

MATERIALS TO AVOID: Strong oxidizing agents.

HAZARDOUS DECOMPOSITION PRODUCTS: Thermal decomposition products may include carbon monoxide, carbon dioxide, and other petroleum decomposition products (hydrocarbons).

HAZARDOUS POLYMERIZATION: Has not been reported to occur under normal temperatures and pressures.

Section 11 - TOXICOLOGY INFORMATION

Note: CHS has not conducted specific toxicity tests on this product.

Section 12 - ECOLOGICAL INFORMATION

Note: CHS has not conducted specific ecological tests on this product.

Section 13 - DISPOSAL CONSIDERATION

WASTE DISPOSAL PROCEDURES: Place contaminated materials in a disposable container and dispose of in accordance with Local, State and Federal environmental regulations. Recycle as much of the recovered product as possible. Do not flush to drain or storm sewer or otherwise release to the environment.

Section 14 - TRANSPORTATION

DOT PROPER SHIPPING NAME: Fuel Oil #2

DOT HAZARD CLASS: Combustible Liquid

DOT IDENTIFICATION NUMBER: NA 1993

DOT EMER. RESPONSE GUIDE NO.: 128

(formerly # 27)

Proper Shipping Name-Fuel Oil #2; Hazard Class-3; UN/NA Identification #-NA1993; Packing Group-III; Placard-Combustible Liquid

Section 15 - REGULATORY INFORMATION

This product does not contain toxic chemicals subject to the reporting requirements of SARA Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 and of 40 CFR 372.

CAS Number
Chemical Name
Percent by Weight
SARA SECTION 311-312 HAZARD CATEGORIES (40 CFR 370.2):
FIRE: Yes
SUDDEN RELEASE OF PRESSURE: No
REACTIVE: No
ACUTE: Yes
CHRONIC: Yes



MATERIAL SAFETY DATA SHEET

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

CHS Inc.
P.O. Box 64089
Mail station 525
St. Paul, MN 55164-0089

Transportation Emergency (CHEMTREC): 1-800-424-9300
Technical Information: 1-651-355-8443
MSDS Information: 1-651-355-8438

PRODUCT NAME: Propane

MSDS: 0148-M7A0 - Rev. G (12/19/07)

COMMON NAME: Propane, Liquefied Petroleum Gas;
LP Gas; Dimethyl methane

CHEMICAL FORMULA: C₃H₈

CHEMICAL NAME: Dimethylmethane

CHEMICAL FAMILY: Paraffin Hydrocarbons

Section 2 - COMPOSITION AND INFORMATION ON INGREDIENTS

INGREDIENTS	PERCENTAGES (by weight)	PEL (OSHA)	TLV (ACGIH)	CAS #
Propane	95 - 100%	1000 ppm TWA	2500 ppm TWA Simple Asphyxiant	74-98-6
Propylene	0 - 5%	N/D	Simple Asphyxiant	115-07-1

NOTE: Ethyl Mercaptan added as an odorant.

(TWA) - Time Weighted Average is the employer's average airborne exposure in any 8-hour work shift of a 40-hour work week which shall not be exceeded.

(STEL) - Short Term Exposure Limit is the employee's 15-minute time weighted average exposure which shall not be exceeded at any time during a work day unless another time limit is specified.

Section 3 - HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

DANGER! Extremely flammable. Compressed gas. At very high concentrations, can displace the normal air and cause suffocation from lack of oxygen. Liquid can cause burns similar to frostbite. Caution: Ethyl mercaptan used as a warning agent may not be entirely effective in all situations because of a condition commonly referred to as odor fade (see section 10 for more information). If you suspect a leak, use a combustible gas indicator or similar device to check for gas leaks.

OSHA HAZARD CLASS

Based on OSHA definitions, the following ingredients in this product are hazardous. The OSHA physical and health hazard categories are shown below. Note: CHS has not conducted specific toxicity tests on this product. Our hazard evaluation is based on information from similar ingredients, technical literature, and/or professional experience.

Propane - Flammable Gas, Compressed Gas, Asphyxiant

POTENTIAL HEALTH EFFECTS

ROUTES OF ENTRY: Inhalation, Dermal.

ACUTE EFFECTS OF OVER EXPOSURE:

Eyes - Liquid can cause burns similar to frostbite.

Skin - Liquid can cause burns similar to frostbite.

Inhalation - At very high concentrations can displace the normal air and cause suffocation from lack of oxygen. Symptoms of lack of oxygen include increase depth and frequency of breathing, dizziness, headache, nausea or loss of consciousness.

Ingestion - Liquid can cause burns similar to frostbite.

CHRONIC EFFECTS OF OVER EXPOSURE: None Determined

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: Personnel with pre-existing chronic respiratory diseases should avoid exposure to this material

CARCINOGENICITY: NTP: No IARC: No OSHA: No **EMERGENCY AND FIRST AID PROCEDURES:**

Section 4 - FIRST AID MEASURES

Eye Contact - If liquid propane contacts the eye, flush thoroughly with water for at least 15 minutes, occasionally lifting the upper and lower lids, until no evidence of chemical remains. Get medical attention as soon as possible.

Skin Contact - Frozen tissue should be flushed with plenty of tepid water. Do not use hot water. Cryogenic (low temperature) burns which result in blistering or deeper tissue freezing should be promptly treated by a physician.

Inhalation - Move person to fresh air. If large amounts have been inhaled, keep victim warm and get medical attention. Apply artificial respiration if not breathing.

Ingestion -

Section 5 - FIRE - FIGHTING MEASURES

FLASH POINT: -156°F

AUTO IGNITION TEMP: 874°F

FLAMMABLE LIMITS IN AIR
% BY VOLUME

<u>LOWER</u>	<u>UPPER</u>
2.1	9.5

EXTINGUISHING MEDIA: Do not extinguish gas fire unless the gas leak can be stopped. For small fire use dry chemical or Carbon Dioxide (CO₂). For large fires, use water spray or fog and move containers from fire area if you can do so without risk.

SPECIAL FIRE FIGHTING PROCEDURES: Shut off gas source and allow the fire to burn itself out. Gas fires should not be extinguished unless the gas flow can be stopped immediately. Keep unnecessary people away; isolate hazard area and deny entry. Stay upwind, out of low areas, and ventilate closed spaces before entering. Positive pressure self-contained breathing apparatus (SCBA) and structural firefighters' protective clothing will provide limited protection.

FIRE INVOLVING TANK, RAIL CAR, OR TANK TRUCK: Isolate for 1600 meters (1 mile) in all directions; also, consider initial evacuation for 1600 meters (1 mile) in all directions Call CHEMTREC at 1-800-424-9300 as soon as possible, especially if there is no local hazardous materials team available. If gas source cannot be shut off immediately, fight fire from maximum distance or use unmanned hose holders or monitor nozzles. Cool container with flooding quantities of water until well after fire is out to prevent container from exploding. ALWAYS stay away from tanks engulfed in fire. WITHDRAW IMMEDIATELY in case of rising sound from venting safety devices or discoloration of tank. For massive fire, use unmanned hose holders or monitor nozzles; if this is impossible, withdraw from area and let fire burn.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Vapors are heavier than air and may travel along the ground and collect in low or confined areas and be exposed to a source of ignition (pilot light, heater, electric motor) some distance away. Withdraw immediately in case of rising sound from venting safety devices or any discoloration of tank due to fire.

HAZARD RATINGS:	NFPA 704:	Health- <u>1</u>	Fire- <u>4</u>	Reactivity- <u>0</u>
	HMIS:	Health- <u>1</u>	Fire- <u>4</u>	Reactivity- <u>0</u>

Section 6 - ACCIDENTAL RELEASE MEASURES

STEPS TO TAKE IF MATERIAL IS RELEASED OR SPILLED: ELIMINATE ALL SOURCES OF IGNITION AND STOP LEAK IF YOU CAN DO SO WITHOUT RISK. Notify emergency response personnel as appropriate. Keep unnecessary people away; isolate hazard area and deny entry. Vapors can be dispersed with sustained water spray. Prevent spreading of vapors through sewers, ventilation systems and confined areas. NOTE: Review Section 5 -FIRE-FIGHTING MEASURES before proceeding with clean up. Use appropriate personal protective equipment during emergency response.

Section 7 - HANDLING AND STORAGE

HANDLING AND STORING: Consult the U.S. Department of Transportation regulations on the shipping of petroleum gases. If upon initial receipt inspection a cylinder is found to be in poor condition, contact the supplier. The most common hazard is leakage due to faulty pressure control regulators. Large pressure build-up can result in explosive decompression at the cylinder head, causing the cylinder to rocket like a missile. Prevent entrapment of liquid in closed system. Use check valve to prevent back-flow into storage container. Chain cylinders when not in use. Cylinder storage should be segregated from oxidizers such as oxygen, chlorine, etc. and away from heavy traffic areas to prevent knocking over or damage from falling objects. Valve caps should remain on cylinders.

Section 8 - EXPOSURE CONTROL - PERSONAL PROTECTION

ENGINEERING CONTROLS: Local exhaust and general ventilation may both be necessary in work area to prevent accumulation of explosive mixtures. Provide special ventilation in sumps and confined spaces. If mechanical ventilation is used, electrical equipment must meet National Electrical Code requirements.

RESPIRATORY EQUIPMENT: Personnel should never enter an area of high concentration without proper respiratory protection. Provide NIOSH-approved air-supplied respirator or self-contained breathing apparatus for emergency or non-routine situations where the level is excessive.

EYE PROTECTION: Use face shield or chemical type goggles where contact with material may occur such as when changing valves, hoses, etc.

PROTECTIVE CLOTHING: Use protective clothing, face shield, and gloves when contact with liquid propane is possible.

OTHER (SAFETY SHOWERS, EYE WASH STATIONS, ETC.): Emergency eye wash fountains and safety showers for first aid treatment of potential freeze burns should be available in the vicinity of any significant exposure from compressed gas release.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: Colorless gas (liquid under pressure)

ODOR: If odorized, will have rotten egg odor, otherwise odorless.

BOILING POINT: 760 mmHg @ -44°F

SPECIFIC GRAVITY (water=1): 0.5

VAPOR PRESSURE: 190 psia @ 100°F

VAPOR DENSITY (air=1): 1.5

SOLUBLE IN WATER: Very slightly soluble

EVAPORATION RATE (ether=1): N/A

pH:

Section 10 - STABILITY AND REACTIVITY

STABILITY -

STABLE X (At normal temperature and storage conditions)

UNSTABLE

INCOMPATIBILITY -

CONDITIONS TO AVOID: Propane vapors will form explosive mixtures with air and will easily ignite by heat, sparks, flames, build-up of static electricity, and other sources of ignition. Note: Ethyl mercaptan might, under certain conditions (when oxygen, water, iron oxide or other oxidizers are present in containers and piping) react with oxidizers which diminish or eliminate entirely its distinct smell, thereby reducing or eliminating the ability of a person to detect a leak. The passage of odorized propane through soil because of an underground leak will also diminish or eliminate entirely the smell of odorized propane. If you suspect a leak, use a combustible gas indicator or similar device to check for gas leaks.

MATERIALS TO AVOID: Strong acids, alkalies and oxidizers such as chlorine (gas or liquid) and oxygen.

HAZARDOUS DECOMPOSITION PRODUCTS: Normal combustion produces carbon dioxide; incomplete combustion can produce carbon monoxide.

HAZARDOUS POLYMERIZATION: Has not been reported to occur.

Section 11 - TOXICOLOGY INFORMATION

Note: CHS has not conducted specific toxicity tests on this product.

Section 12 - ECOLOGICAL INFORMATION

Note: CHS has not conducted specific ecological tests on this product.

Section 13 - DISPOSAL CONSIDERATION

WASTE DISPOSAL PROCEDURES: Releases are expected to cause only localized non-persistent environmental damage. Waste mixtures containing these gases should not be allowed to enter drains or sewers where there is danger of vapors being ignited. When it becomes necessary to dispose of these gases, it is preferable to do so as a vapor. These gases may be used as an auxiliary fuel or disposed of by flaring in a properly designed flare or incinerator. Venting of the gases to the atmosphere should be avoided. Treatment, storage, transportation and disposal must be in accordance with applicable federal, state and local regulations.

Section 14 - TRANSPORTATION

DOT PROPER SHIPPING NAME: Liquefied Petroleum Gas

DOT HAZARD CLASS: 2.1

DOT IDENTIFICATION NUMBER: UN 1075

DOT EMER. RESPONSE GUIDE NO.: 115
(Formerly #22)

DOT LABEL, PLACARD: Flammable Gas

Section 15 - REGULATORY INFORMATION

This product may contain the following toxic chemicals subject to the reporting requirements of SARA Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 and of 40 CFR 372.

<u>Cas Number</u>	<u>Chemical Name</u>	<u>Percent By Weight</u>
115-07-1	Propylene	0 - 5%

SARA SECTION 311-312 HAZARD CATEGORIES (40 CFR 370.2):

FIRE: Yes **SUDDEN RELEASE OF PRESSURE:** Yes **REACTIVE:** No **ACUTE:** Yes **CHRONIC:** No